TLW 0319 Project No. 24/095

S.A.A.M.I. JAR-OFF, DROP & ROTATION TEST

SAAMI Specifications for Standard Drop Test:

Drop Test:

48-inch drop - onto 1" thick 85 durameter (Shore A) Rubber Matt Firearm not ready to fire, Safe in "Safe" position, Fresh Primed Case in Chamber, Magazine loaded to capacity with Dummy Rounds. After each drop Fire Primed Case to verify firearm will still function.

48 inch drop (safety in "Safe" position) - one drop per orientation.

Note: for Firearms with the ISS system installed - The Firearms will be set with the

ISS system in	the unlocked position for all six o	orientations of the Drop Test
Orientation	ISS Unlocked	Comments
Barrel Vertical, Muzzle Up:	PassFail	
Barrel Vertical, Muzzle Down:	Pass Fail	
Barrel Horizontal, Left side of S	Stock Up: Pass Fail	
Barrel Horizontal, Right side of	Stock Up: PassFail	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
Barrel Horizontal, Bottom of St	ock Up: Pass Fail	
Barrel Horizontal, Bottom of St	ock Down: Pass V Fail	
	ons for Standard Rotation Test est Firegrm on the Butt end and a	llow Firearm to fall
	Proprionto 1" thick 85 durameter	
	a Chamber, Magazine loaded to co	to verify firearm will still function.
(日本) (日本)		The Firearms will be set with the
	the unlocked position for both ori	/
Orientation	ISS Unlocked	Comments
Firearm Vertical, Drop so left s	ide of Stock is Up: Pass V Fai	il
Firearm Vertical, Drop so right	side of Stock is Up: Pass Fail	
Notes: (continue on back of sheet if	necessary)	
		Tester's Initials JTQ
		Page 2 of 2 Z101\DROPTEST_REV3.DOO

ET08271