

TLW 9172E
Project No. 241095

Page 1 of 2

S.A.A.M.I. JAR-OFF, DROP & ROTATION TEST

Firecontrol No. _____ Firecontrol Type: _____ Date: 6/16/99

Dry Cycles/Rounds Completed: _____ Stock Type S&W Engagement at Start _____

Model No. M/71c Serial No. XC - 1057 Engagement at End _____

Trigger Pull at Start of Test (1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (6) _____

Average Trigger Pull at Start of Test: _____ Std. Dev. of Trigger Pull at Start of Test: _____

Trigger Pull at End of Test (1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (6) _____

Average Trigger Pull at End of Test: _____ Std. Dev. of Trigger Pull at End of Test: _____

Additional Notes and Comments

For additional details on the proper procedures to be used for this Test Procedure refer to:

ANSI / SAAMI Z299.5-1990

SAAMI Specifications for Standard Jar-Off Test:

*Jar-Off Test: 12 inch drop - onto 1" thick 85 durometer (Shore A) Rubber Matt
Firearm ready to fire, Safe in "Fire" position, Fresh Primed Case in
Chamber, Magazine loaded to capacity with Dummy Rounds.
After each drop Fire Primed Case to verify firearm will still function.*

12 inch drop (safety in "Fire" position) - one drop per orientation.

Comments

Barrel Horizontal, Bottom of Stock Down :	Pass <input checked="" type="checkbox"/>	Fail <input type="checkbox"/>	
Barrel Horizontal, Bottom of Stock Up :	Pass <input type="checkbox"/>	Fail <input checked="" type="checkbox"/>	<u>Fired Primed Case</u>
Barrel Horizontal, Left side of Stock Up :	Pass <input checked="" type="checkbox"/>	Fail <input type="checkbox"/>	
Barrel Horizontal, Right side of Stock Up :	Pass <input checked="" type="checkbox"/>	Fail <input type="checkbox"/>	
Barrel Vertical, Muzzle Up :	Pass <input checked="" type="checkbox"/>	Fail <input type="checkbox"/>	
Barrel Vertical, Muzzle Down :	Pass <input checked="" type="checkbox"/>	Fail <input type="checkbox"/>	

11.845 lbs

ET19759