Test Lab Work Request Form

1.-

Date Submitted: 19 May, 1999	Tracking #: TLW 9142I
Project #: 241095	Engineer: SNEDEKER, J.R.
Test Objective: COMPLETE STANDARD S.A.A.M.I. DI ON EACH OF THE M/710 EET SAMPI ON 18 MAY '99. Test Description: 1. Perform standard procedure, S all submitted samples of M/71 using standard S.A.A.M.I. pro- fresh primed case for each drop primed case after each drop to 2. Use the standard forms for S.A. procedure for recording the re-	ROP, JAR-OFF AND ROTATION TESTING LE RIFLES SUBMITTED FOR EVALUATIO S.A.A.M.I. Drop, Jar-Off And Rotation Testing on 0 EET rifles. Examine each rifle after each drop ocedures. Load chamber and close bolt over a op, jar-off or rotation orientation. "Fire" the make sure the round did not fire when dropped. A.A.M.I. Drop, Jar-Off And Rotation Testing sults. In addition to the test results, and as a ould list the tester's initials the date, the beginnin
and ending round level covered	ed by that data sheet. Also, the "TLW" number
 the serial number of the firear type used when the malfunction 3. Due to the construction of the modification. Before proceed the engineer technician and to be used. 	ed by that data sheet. Also, the "TLW" number m and the sample number and the ammunition on occurred should be recorded on each data shee ISET samples, the drop procedure may require ing with this test, discussion should occur betwee esting manager to determine the proper methods t
 the serial number of the firear type used when the malfunction 3. Due to the construction of the modification. Before proceed the engineer technician and to be used. 	m and the sample number and the ammunition on occurred should be recorded on each data shee RET samples, the drop procedure may require ing with this test, discussion should occur betwee esting manager to determine the proper methods t
the serial number of the firear type used when the malfunction 3. Due to the construction of the modification. Before proceed the engineer technician and to be used.	m and the sample number and the ammunition on occurred should be recorded on each data shee FET samples, the drop procedure may require ing with this test, discussion should occur betwee esting manager to determine the proper methods t Test Results Required: Formal Report: Data Only: X
the serial number of the firear type used when the malfunction 3. Due to the construction of the modification. Before proceed the engineer technician and to be used.	m and the sample number and the ammunition on occurred should be recorded on each data shee EET samples, the drop procedure may require ing with this test, discussion should occur betwee esting manager to determine the proper methods to Test Results Required: Formal Report: Data Only: X REQUESTED Completion Date:
the serial number of the firear type used when the malfunction 3. Due to the construction of the modification. Before proceed the engineer technician and to be used.	m and the sample number and the ammunition on occurred should be recorded on each data shee INET samples, the drop procedure may require ing with this test, discussion should occur betwee esting manager to determine the proper methods to Test Results Required: Formal Report: Data Only: X REQUESTED Completion Date: 28 May '99
the serial number of the firear type used when the malfunction 3. Due to the construction of the modification. Before proceed the engineer technician and to be used. Resource Usage: Manpower Requirements - 1 technician Facility Requirements - Required Materials/Parts/Equipment (inter- Approximately 120 rounds of standard .30- to make primed cases. 85 durameter rubber mat.	m and the sample number and the ammunition on occurred should be recorded on each data shee ISET samples, the drop procedure may require ing with this test, discussion should occur betwe esting manager to determine the proper methods Test Results Required: Formal Report: Data Only: X REQUESTED Completion Date: 28 May '99 clude quantities): D6 ammunition, with bullets and powder removed
the serial number of the firear type used when the malfunction 3. Due to the construction of the modification. Before proceed the engineer technician and to be used.	m and the sample number and the ammunition on occurred should be recorded on each data shee EET samples, the drop procedure may require and with this test, discussion should occur betwee esting manager to determine the proper methods the sting manager to determine the proper methods Test Results Required: Formal Report: Data Only: X REQUESTED Completion Date: 28 May '99 clude quantities): D6 ammunition, with bullets and powder removed
the serial number of the firear type used when the malfunction 3. Due to the construction of the modification. Before proceed the engineer technician and to be used. Resource Usage: Manpower Requirements - 1 technician Facility Requirements - Required Materials/Parts/Equipment (inter- Approximately 120 rounds of standard .30- to make primed cases. 85 durameter rubber mat.	m and the sample number and the ammunition on occurred should be recorded on each data shee ISET samples, the drop procedure may require ing with this test, discussion should occur betwee esting manager to determine the proper methods string manager to determine the proper methods Test Results Required: Formal Report: Data Only: X REQUESTED Completion Date: 28 May '99 clude quantities): 06 ammunition, with bullets and powder removed

.