

TLW 0395
Project No. 241095

Page 1 of 2
JW

S.A.A.M.I. JAR-OFF, DROP & ROTATION TEST

Firecontrol No. _____ Firecontrol Type: Std. Date: 1-17-01
Dry Cycles/Rounds Completed: _____ Stock Type Syn. Engagement at Start .0199
Model No. 710 Serial No. 71002467 Engagement at End .0197
Trigger Pull at Start of Test (1) 4.50 (2) 4.25 (3) 4.25 (4) 4.25 (5) 4.25 (6) 4.0
Average Trigger Pull at Start of Test: 4.25 Std. Dev. of Trigger Pull at Start of Test: _____
Trigger Pull at End of Test (1) 4.0 (2) 4.25 (3) 4.25 (4) 4.25 (5) 4.5 (6) 4.5
Average Trigger Pull at End of Test: 4.29 Std. Dev. of Trigger Pull at End of Test: _____

Additional Notes and Comments

For additional details on the proper procedures to be used for this Test Procedure refer to:

ANSI / SAAMI Z299.5-1990

SAAMI Specifications for Standard Jar-Off Test:

Jar-Off Test: 12 inch drop - onto 1" thick 85 durometer (Shore A) Rubber Matt
Firearm ready to fire, Safe in "Fire" position, Fresh Primed Case in
Chamber, Magazine loaded to capacity with Dummy Rounds.
After each drop Fire Primed Case to verify firearm will still function.

12 inch drop (safety in "Fire" position) - one drop per orientation.

		Comments
Barrel Horizontal, Bottom of Stock Down:	Pass <input checked="" type="checkbox"/> Fail _____	_____
Barrel Horizontal, Bottom of Stock Up:	Pass <input checked="" type="checkbox"/> Fail _____	_____
Barrel Horizontal, Left side of Stock Up:	Pass <input checked="" type="checkbox"/> Fail _____	_____
Barrel Horizontal, Right side of Stock Up:	Pass <input checked="" type="checkbox"/> Fail _____	_____
Barrel Vertical, Muzzle Up:	Pass <input checked="" type="checkbox"/> Fail _____	_____
Barrel Vertical, Muzzle Down:	Pass <input checked="" type="checkbox"/> Fail _____	_____

ET19939

TLW 0395
Project No. 241095

Page 2 of 2

S.A.A.M.I. JAR-OFF, DROP & ROTATION TEST (cont'd)

SAAMI Specifications for Standard Drop Test:

Drop Test: 48 inch drop - onto 1" thick 85 durameter (Shore A) Rubber Matt
Firearm not ready to fire, Safe in "Safe" position, Fresh Primed Case
in Chamber, Magazine loaded to capacity with Dummy Rounds.
After each drop Fire Primed Case to verify firearm will still function.

48 inch drop (safety in "Safe" position) - one drop per orientation.

	Pass	Fail	Comments
Barrel Horizontal, Bottom of Stock Down :	Pass <input checked="" type="checkbox"/>	Fail <input type="checkbox"/>	
Barrel Horizontal, Bottom of Stock Up :	Pass <input checked="" type="checkbox"/>	Fail <input type="checkbox"/>	
Barrel Horizontal, Left side of Stock Up :	Pass <input checked="" type="checkbox"/>	Fail <input type="checkbox"/>	
Barrel Horizontal, Right side of Stock Up :	Pass <input checked="" type="checkbox"/>	Fail <input type="checkbox"/>	
Barrel Vertical, Muzzle Up :	Pass <input checked="" type="checkbox"/>	Fail <input type="checkbox"/>	
Barrel Vertical, Muzzle Down :	Pass <input checked="" type="checkbox"/>	Fail <input type="checkbox"/>	

SAAMI Specifications for Standard Rotation Test:

Rotation Test: Rest Firearm on the Butt end and allow Firearm to Fall
Drop - onto 1" thick 85 durameter (Shore A) Rubber Matt
Firearm not ready to fire, Safe in "Safe" position, Fresh Primed Case
in Chamber, Magazine loaded to capacity with Dummy Rounds.
After each drop Fire Primed Case to verify firearm will still function.

"Rotation" (safety in "Safe" position) - one drop per orientation.

	Pass	Fail	Comments
Firearm Vertical, Drop so Left side of Stock is Up :	Pass <input checked="" type="checkbox"/>	Fail <input type="checkbox"/>	
Firearm Vertical, Drop so Right side of Stock is Up :	Pass <input checked="" type="checkbox"/>	Fail <input type="checkbox"/>	

Notes:

Tester Initials: JW + EP

ET19940