

CAL: 300 WIN MAG

TRACKING # TLW 1407
PROJECT # 241314

[illegible]

Logform

3

Confidential - Subject to Protective Order
Williams v. Remington

CONFIDENTIAL

Remington Arms Company Inc.
Research & Development Technical Center
315 West Ring Road
Elizabethtown, KY 42701

Clean & Inspect Checklist

Model: 710 Magnum

Project: 241314

Rifle: A-1

TLW #: TLW1303

Date: 3, 12, 104

Inspector: J. Sims

Round Level: 701

- ☒ Measure Headspace Min +.004
- ☒ Inspect Take Down Screws for loosening. Center screw, 1/4 turn loosened.
- ☒ Sear Engagement: 1st. .0340 2nd. .0339 3rd. .0341 Ave. .0340 spec- .025" to .030"
- ☒ Reset Sear Engagement if Required: 1st. .0254 2nd. .0253 3rd. .0255 Ave. .0254
- ☒ Trigger Pull: 1st. 4.364 2nd. 4.091 3rd. 4.070 Ave. 4.010 spec- 4.5 lb. to 5.5 lb.
- ☒ Reset Trigger Pull if Required: 1st. 5.001 2nd. 5.142 3rd. 5.052 Ave. 5.049
- ☒ Inspect cam surface, locking lugs and bolt stop for signs of excessive wear: Cam surface, locking lugs, bolt stop, all have some wear.
- ☒ Inspect stock for any signs of cracking or other failure: Stock is cracked where center Takedown screw threads into.

☐ Other items of

note:

TLW1216

Remington Confidential

ET21065

CONFIDENTIAL

Remington Arms Company Inc.
Research & Development Technical Center
315 West Ring Road
Elizabethtown, KY 42701

Clean & Inspect Checklist

Model: 710 Magnum

Project: 241314

Rifle: A-1

TLW #: TLW1303

Date: 3 15 04

Inspector: BL

Round Level: 1201

- ☒ Measure Headspace min .004
- ☒ Inspect Take Down Screws for loosening. no movement
- ☒ Sear Engagement: 1st .0273 2nd .0289 3rd .0297 Ave. .0286 spec- .025" to .030"
- ☐ Reset Sear Engagement if Required: 1st ~ 2nd ~ 3rd ~ Ave. ~
- ☒ Trigger Pull: 1st 5.009 2nd 5.018 3rd 4.850 Ave. 4.959 spec- 4.5 lb. to 5.5 lb.
- ☐ Reset Trigger Pull if Required: 1st ~ 2nd ~ 3rd ~ Ave. ~
- ☒ Inspect cam surface, locking lugs and bolt stop for signs of excessive wear: cam surface, locking lugs, bolt stop some signs of wear
- ☒ Inspect stock for any signs of cracking or other failure: stock cracked at center screw hole
- ☒ Other items of note: Torque Top take down screw to 75 in. Lb.

TLW1216

Remington Confidential

ET21066