

CONFIDENTIAL

Remington Arms Company Inc.
Research & Development Technical Center
315 West Ring Road
Elizabethtown, KY 42701

Clean & Inspect Checklist

Model: 710 Magnum

Project: 241314

Rifle: A-27

TLW #: TLW1303

Date: 3 14 104

Inspector: BL

Round Level: 901

- ☒ Measure Headspace min +.005
- ☒ Inspect Take Down Screws for loosening. Top screw 8 turn
- ☒ Sear Engagement: 1st. .0278 2nd. .0286 3rd. .0285 Ave. .0283 spec- .025" to .030"
- ☒ Reset Sear Engagement if Required: 1st. 2nd. 3rd. Ave.
- ☒ Trigger Pull: 1st. 5.001 2nd. 5.047 3rd. 5.087 Ave. 5.045 spec- 4.5 lb. to 5.5 lb.
- ☒ Reset Trigger Pull if Required: 1st. 2nd. 3rd. Ave.
- ☒ Inspect cam surface, locking lugs and bolt stop for signs of excessive wear: Cam surface, locking lugs, some sign of wear
Bolt stop excessive wear
- ☒ Inspect stock for any signs of cracking or other failure: Cracked stock at center screw hole
- ☐ Other items of note:

TLW1216

Remington Confidential

ET21121