

CONFIDENTIAL

Remington Arms Company Inc.
Research & Development Technical Center
315 West Ring Road
Elizabethtown, KY 42701

Clean & Inspect Checklist

Model: 710 Magnum

Project: 241314

Rifle: A-1

TLW #: TLW 1436

Date: 3 / 15 / 04

Inspector: SW/BL

Round Level: 151

☒ Measure Headspace Min +.002 When GO Gauge went (will not go.) 83

☒ Inspect Take Down Screws for loosening. Top Take down Screw 1/8" movement

☒ Sear Engagement: 1st .0338 2nd .0327 3rd .0329 Ave. .0330 spec- .025" to .030"

☐ Reset Sear Engagement if Required: 1st _____ 2nd _____ 3rd _____ Ave. _____

☒ Trigger Pull: 1st 4.922 2nd 4.914 3rd 4.918 Ave. 4.918 spec- 4.5 lb. to 5.5 lb.

☐ Reset Trigger Pull if Required: 1st _____ 2nd _____ 3rd _____ Ave. _____

☒ Inspect cam surface, locking lugs and bolt stop for signs of excessive wear: Cam surface, Locking Lugs some sign of wear

☒ Inspect stock for any signs of cracking or other failure: No cracks

☐ Other items of note: _____

TLW 1436

Remington Confidential

ET21477