

CONFIDENTIAL

Remington Arms Company Inc.
Research & Development Technical Center
315 West Ring Road
Elizabethtown, KY 42701

Clean & Inspect Checklist

Model: 710 Magnum 7mm RM

Project: 241314

Rifle: A-13

TLW #: TLW1447

Date: 5 / 18 / 04

Inspector: SW

Round Level: 701

- ☒ Measure Headspace Min +.002
- ☒ Inspect Take Down Screws for loosening. Front Screw 1/4 Turn
- ☒ Sear Engagement: 1st .0338 2nd .0336 3rd .0335 Ave. .03363 spec- .025" to .030"
- ☐ Reset Sear Engagement if Required: 1st 2nd 3rd Ave.
- ☒ Trigger Pull: 1st 4.072 2nd 4.090 3rd 4.044 Ave. 4.069 spec- 4.5 lb. to 5.5 lb.
- ☒ Reset Trigger Pull if Required: 1st 5.025 2nd 5.017 3rd 5.006 Ave. 5.025
- ☒ Inspect cam surface, locking lugs and bolt stop for signs of excessive wear: OK
- ☒ Inspect stock for any signs of cracking or other failure: OK
- ☐ Other items of note:

TLW1216

Remington Confidential

ET21610