

NAME	DATE	TEST ACTIVITY	COMMENTS	ROUNDS AT START-	
				RDS. FIRED	TOTAL RDS.
SW/JS	4/25/04	Head space	Min +.004	TLW1447A	
"	"	Head space	Belt Type GO won't close	"	
SW/JS	4/25/04	Proof & Rd	OK	TLW1447B	1
↓	4/26/04	Head space	Min +.004	TLW1447C	
"	"	Head space	Belt Type GO won't close	"	
SW	4/26/04	Firing Pin Indent	.019, .019, .019 Avg .0190	TLW1447D	
↓	4/27/04	Check Loosening	Torque Front screw 37 in lbs	TLW1447Z	
↓	↓	Check Depth of	Front take down screw hole .0840	↓	
↓	↓	Check number of turns to loosen front screw	1 3/4 Turns	↓	
↓	↓	Inspect threads & measure length	OK / 1.4495	TLW1447E	
↓	↓	Engagement	.0355, .0353, .0356 Avg .03546	TLW1447F	
↓	↓	Trigger Pull	5.005, 5.174, 5.188, 4.993, 5.012 Avg 5.074	"	
SW	4/28/04	Serv list	.0185	TLW1447E	
SW	4/29/04	Torque Front screw	70 in lbs	TLW1447	
SW	4/30/04	200 Rd Basic Arch Function Test		TLW1447D	200
BL	5-6-04	Clean Bore & Bolt			
SW	5/13/04	EX-Function & Endurance test	1000 Functions	TLW1447R	200
SW	5/18/04	Clean & Inspect	Head space Min +.005	TLW1447S	701

THIS SHEET IS TO ACCOMPANY THE FIREARM AT ALL TIMES THROUGHOUT TESTING

FORMS.XLS