

CONFIDENTIAL

Remington Arms Company Inc.  
Research & Development Technical Center  
315 West Ring Road  
Elizabethtown, KY 42701

## Clean & Inspect Checklist

Model: 710 Magnum 7mm RM

Project: 241314

Rifle: A-18

TLW #: TLW1447

Date: 5 / 18 / 04

Inspector: SW

Round Level: 701

- ☒ Measure Headspace Min +.005
- ☒ Inspect Take Down Screws for loosening. Front screw 0 Turn
- ☒ Sear Engagement: 1<sup>st</sup>. .0374 2<sup>nd</sup>. .0378 3<sup>rd</sup>. .0377 Ave. .03763 spec- .025" to .030"
- ☐ Reset Sear Engagement if Required: 1<sup>st</sup>. \_\_\_\_\_ 2<sup>nd</sup>. \_\_\_\_\_ 3<sup>rd</sup>. \_\_\_\_\_ Ave. \_\_\_\_\_
- ☒ Trigger Pull: 1<sup>st</sup>. 4.533 2<sup>nd</sup>. 4.539 3<sup>rd</sup>. 4.551 Ave. 4.538 spec- 4.5 lb. to 5.5 lb.
- ☐ Reset Trigger Pull if Required: 1<sup>st</sup>. \_\_\_\_\_ 2<sup>nd</sup>. \_\_\_\_\_ 3<sup>rd</sup>. \_\_\_\_\_ Ave. \_\_\_\_\_
- ☒ Inspect cam surface, locking lugs and bolt stop for signs of excessive wear: OK
- ☒ Inspect stock for any signs of cracking or other failure: OK
- ☐ Other items of note: \_\_\_\_\_

TLW1216

Remington Confidential

ET21672