

CONFIDENTIAL

Remington Arms Company Inc.  
Research & Development Technical Center  
315 West Ring Road  
Elizabethtown, KY 42701

## Clean & Inspect Checklist

Model: 710 Magnum 7mm RM

Project: 241314

Rifle: A-72

TLW #: TLW1447

Date: 5 / 19 / 04

Inspector: SW

Round Level: 701

- ☒ Measure Headspace Min + .001
- ☒ Inspect Take Down Screws for loosening. Front Screw 1/16 Turn
- ☒ Sear Engagement: 1<sup>st</sup>. .0368 2<sup>nd</sup>. .0372 3<sup>rd</sup>. .0372 Ave. .03706 spec. .025" to .030"
- ☐ Reset Sear Engagement if Required: 1<sup>st</sup>. \_\_\_\_\_ 2<sup>nd</sup>. \_\_\_\_\_ 3<sup>rd</sup>. \_\_\_\_\_ Ave. \_\_\_\_\_
- ☒ Trigger Pull: 1<sup>st</sup>. 4.696 2<sup>nd</sup>. 4.750 3<sup>rd</sup>. 4.661 Ave. 4.702 spec- 4.5 lb. to 5.5 lb.
- ☐ Reset Trigger Pull if Required: 1<sup>st</sup>. \_\_\_\_\_ 2<sup>nd</sup>. \_\_\_\_\_ 3<sup>rd</sup>. \_\_\_\_\_ Ave. \_\_\_\_\_
- ☒ Inspect cam surface, locking lugs and bolt stop for signs of excessive wear: OK
- ☒ Inspect stock for any signs of cracking or other failure: OK
- ☐ Other items of note: \_\_\_\_\_

TLW1216

Remington Confidential

ET21723