

NAME	DATE	TEST ACTIVITY	COMMENTS	ROUNDS AT START-	
				RDS. FIRED	TOTAL RDS.
SW/JS	4/25/04	Head space	Min .003	TLW1447A	
"	"	Head space	Belt Type GO	"	
SW/JS	4/25/04	Prop & Rd	OK	TLW1447B	1
↓	4/26/04	Head space	Min .004	TLW1447C	
↓	"	Head space	Belt Type GO	"	
SW	4/26/04	Firing Pin Indent	.018, .018, .018 Avg .0180	TLW1447D	
↓	4/28/04	Check Loosening torque front screw	43 in lbs	TLW1447Z	
↓		Check Depth of front take down screw hole	.0142		
↓		Check number of turns to loosen front screw	1 3/4 Turns		
↓		Inspect threads & measure length	OK / 1.4445		
↓		Engagement	.0341, .0341, .0343 Avg .03416	TLW1447E	
↓		Trigger Pull	5.144, 5.132, 5.133, 5.099, 5.187 Avg 5.143	TLW1447F	
SW	4/28/04	Bear 1st	.0156	TLW1447E	
SW	4/29/04	Torque Front screw		TLW1447	
SW	5/3/04	200 lb Basic Jack Function Test		TLW1447P	200
BL	5-6-04	Clean Barrel Bolt			
BL	5-13-04	B.T. Function & Endurance Test	0-Min Functions	TLW1447R	500
SW	5/19/04	Clean & Inspect Head space	Min .004	TLW1447S	201

THIS SHEET IS TO ACCOMPANY THE FIREARM AT ALL TIMES THROUGHOUT TESTING

FORMS.XLS