

CONFIDENTIAL

Remington Arms Company Inc.  
Research & Development Technical Center  
315 West Ring Road  
Elizabethtown, KY 42701

## Clean & Inspect Checklist

Model: 710 Extruded Receiver "Magnum Caliber"

Project: 241314

TLW #: TLW1689

Date: 2 / 22 / 05

Gun Test # A-34

S/N 71202778

Round Level: \_\_\_\_\_

Inspector: BLEE

83

- ☒ Measure Headspace min<sup>+</sup>.004.
- ☒ Check Takedown Screw Torque @ Disassembly: Frt 3, Center 15, Rear 10.
- ☒ Sear Engagement: 1<sup>st</sup>. .0292 2<sup>nd</sup>. .0290 3<sup>rd</sup>. .0299 Ave. .02936 spec-.025" to .030"
- ☐ Reset Sear Engagement if Required: 1<sup>st</sup>. \_\_\_\_\_ 2<sup>nd</sup>. \_\_\_\_\_ 3<sup>rd</sup>. \_\_\_\_\_ Ave. \_\_\_\_\_
- ☒ Trigger Pull: 1<sup>st</sup>. 5.494 2<sup>nd</sup>. 5.522 3<sup>rd</sup>. 5.545 Ave. 5.520 spec- 4.5 lb. to 6 lb.
- ☐ Reset Trigger Pull if Required: 1<sup>st</sup>. \_\_\_\_\_ 2<sup>nd</sup>. \_\_\_\_\_ 3<sup>rd</sup>. \_\_\_\_\_ Ave. \_\_\_\_\_
- ☒ Inspect Firecontrol Insert for any signs of cracking or other failure. OK
- ☐ Other items of note: \_\_\_\_\_
- ☒ Torque Takedown Screws @ Reassembly: SPEC- Frt- 75 in lbs, Center- 30-35 in lbs, Rear- 15 in lbs.

TLW1216

Remington Confidential

ET21963