

CONFIDENTIAL

Remington Arms Company Inc.  
Research & Development Technical Center  
315 West Ring Road  
Elizabethtown, KY 42701

## Clean & Inspect Checklist

Model: 710 Extruded Receiver "Std. Caliber"

Project: 241314

TLW #: TLW1689

Date: 3 / 1 / 05

Gun Test # 4-1

S/N 71202770

Round Level: 1711

Inspector: B. LEE

- ☒ Measure Headspace mint .004
- ☒ Check Takedown Screw Torque @ Disassembly: Frt 25, Center 25, Rear 10
- ☒ Sear Engagement: 1<sup>st</sup> .0248 2<sup>nd</sup> .0249 3<sup>rd</sup> .0249 Ave. .02486 spec- .020" to .025"
- ☐ Reset Sear Engagement if Required: 1<sup>st</sup>      2<sup>nd</sup>      3<sup>rd</sup>      Ave.
- ☒ Trigger Pull: 1<sup>st</sup> 5.364 2<sup>nd</sup> 5.608 3<sup>rd</sup> 5.499 Ave. 5.489 spec- 4 lb. to 5.5 lb.
- ☐ Reset Trigger Pull if Required: 1<sup>st</sup>      2<sup>nd</sup>      3<sup>rd</sup>      Ave.
- ☒ Inspect Firecontrol Insert for any signs of cracking or other failure. OK
- ☐ Other items of note:
- ☒ Torque Takedown Screws @ Reassembly: SPEC- Frt- 50 in lbs, Center- 30-35 in lbs, Rear- 15 in lbs.

TLW1216

Remington Confidential

ET22184