GUN # A-7
REM MODEL 710
SERIAL # 71203239
30.06 CAL.

M/710 EXTRUDED RECEIVER TRIAL AND PILOT # 1

TLW 1689
PROJECT # 241314

NAME	DATE	TEST ACTIVITY	COMMENTS		RDS. FIRED	TOTAL RDS.
B.LEE	1-25-05	Initial Headspace	min .003	TLW1689B		
B.LEE	1-25-05	Proof	OK	TLW1689C	1	1
B.LEE	1-25-05	Headspace	min .004	TLW1689D		
B.LEE	1-26-05	Firing Pin Indent	.021 .020-.022 Avg .021	TLW1689E		
B.LEE	1-28-05	Safe on/off force	See data sheet	TLW1689I		
B.LEE	2-2-05	Sear Eng/Lift	" " "	TLW1689F		
B.LEE	2-3-05	Screw Depth	" " "	TLW1689A		
B.LEE	2-3-05	Trigger Pull	" " "	TLW1689H		
B.LEE	2-4-05	Firing Pin Head Engagement	" " "	TLW1689G		
HJC	2-7-05	Screw De-torque Forces	" " "	TLW1689A		
B.LEE	2-8-05	Torque Screws to Specification	Front 50 in Lb - middle 30-35 in Lb			
			Rear 15 in Lb	TLW1689		
B.LEE	2-9-05	200 Rd Jack Function		TLW1689L	200	201
SW/JS	2/11/05	Set-up	Set Engagement & Trigger For Jar-Off			
SW/JS	2/14/05	5mm Jar-Off	PASS	TLW1689Y		
SW/JS	2/14/05	5mm Rotation	PASS	TLW1689Z		
SW/JS	2/15/05	5mm Drop	Bottom up Higher Trig t	TLW1689AA		
	2/22/05	5mm Drop	Replacer Engagement & Set engagement &			
			trigger pull to finish drop Test.			
			PASS			

THIS SHEET IS TO ACCOMPANY THE FIREARM AT ALL TIMES THROUGHOUT TESTING

FORM DTDS.XLS

Confidential - Subject to Protective Order
Williams v. Remington