

TLW 1216 AAProject No. 241314**EXTENDED ROTATION TEST**

Firecontrol No. A-12 Firecontrol Type: STANDARD Date: 9-19-03  
Dry Cycles/Rounds Completed: \_\_\_\_\_ Stock Type \_\_\_\_\_ Engagement at Start .02030  
Model No. \_\_\_\_\_ Serial No. \_\_\_\_\_ Engagement at End .0206  
Trigger Pull at Start of Test (1) 4.116 (2) 3.982 (3) 4.016 (4) 4.046 (5) 3.985 (6) —  
Average Trigger Pull at Start of Test: 4.029 Std. Dev. of Trigger Pull at Start of Test: \_\_\_\_\_  
Trigger Pull at End of Test (1) 4.539 (2) 4.561 (3) 4.443 (4) 4.576 (5) 4.664 (6) —  
Average Trigger Pull at End of Test: 4.557 Std. Dev. of Trigger Pull at End of Test: \_\_\_\_\_

Tester Initials: \_\_\_\_\_

Additional Notes and Comments

**SAAMI Specifications for Standard Rotation Test do not apply to this test.**

Extended Rotation Test: Rest Firearm on the Butt end and allow Firearm to fall  
Drop - onto Tile Floor backed by Concrete. **NO RUBBER MATT**  
Firearm not ready to fire, Safe in "Safe" position, Fresh Primed Case  
in Chamber, Magazine loaded to capacity with Dummy Rounds.  
After each drop, Fire Primed Case to verify firearm will still function.

"Rotation Test" (safety in "Safe" position) - one drop per orientation.

Note: for Firearms with the ISS system installed - The Firearms will be set with the  
ISS system in the unlocked position for both orientations of the Rotation Test.

Orientation	ISS Unlocked	Comments
Firearm Vertical, Drop so left side of Stock is Up:	Pass <input checked="" type="checkbox"/> Fail _____	_____
Firearm Vertical, Drop so right side of Stock is Up:	Pass <input checked="" type="checkbox"/> Fail _____	_____

Notes: (continue on back of sheet if necessary)

Tester's Initials \_\_\_\_\_