

CONFIDENTIAL

Remington Arms Company Inc.
Research & Development Technical Center
315 West Ring Road
Elizabethtown, KY 42701

Clean & Inspect Checklist

Model: 710 Magnum

Project: 241314

Rifle: A-10

TLW #: TLW1216

Date: 9 / 8 / 03

Inspector: SW/BL

Round Level: 741

- ☒ Measure Headspace Mint .007
- ☒ Sear Engagement: 1st. .0270 2nd. .0271 3rd. .0271 Ave. .02706 spec- .020" to .025" 83
- ☒ Reset Sear Engagement if Required: 1st. .0228 2nd. .0228 3rd. .0227 Ave. .02276
- ☒ Trigger Pull: 1st. 4.428 2nd. 4.382 3rd. 4.515 Ave. 4.442 spec- 4 lb. to 5.5 lb.
- ☒ Reset Trigger Pull if Required: 1st. 4.599 2nd. 4.656 3rd. 4.698 Ave. 4.651
- ☒ Inspect cam surface, locking lugs and bolt stop for signs of excessive wear: Normal wear, wear on bolt stop
- ☒ Inspect stock for any signs of cracking or other failure. cracks in stock
- ☒ Other items of note: Top of magazine box has some protrusion, wear in magazine latch area

TLW1216

Remington Confidential

ET22304