		TLW 1216 AB
		Project No. 241314
EXTENDED DROP TESTING		
Firecontrol No. A-10 P Dry Cycles/Rounds Completed: Model No. Serial No. Trigger Pull at Start of Test (1) 4.16 Average Trigger Pull at Start of Test: Trigger Pull at End of Test (1) 5.006 Average Trigger Pull at End of Test:	(2) 5,066 (3) 5,019 (4	4) Si 2011 (3) 5:0007 (0)
Ado	litional Notes and Comments	Tester Initials:
Primed Ca. Rounds. After the function. all drops (safety Note: for Firearms with the	(%) T(2%) (%) Yak Lag((******	in "Safe" position, Fresh led to capacity with Dummy se to verify firearm will still p per orientation. S will be set in the unlocked
· · · · · · · · · · · · · · · · · · ·	INCH EXTENDED DROP T	<u>EST</u>
 -	S Unlocked	Comments

ET22313

TLW 1216 AB Project No. 241314 **EXTENDED DROP TESTING** A-10 96 INCH EXTENDED DROP TEST Orientation ISS Unlocked Comments Barrel Vertical, Muzzle Up: Pass V Fail Barrel Vertical, Muzzle Down: Pass V Fail Barrel Horizontal, Left side of Stock Up: FIRED Barrel Horizontal, Right side of Stock Up: Fail Pass FIRED Barrel Horizontal, Bottom of Stock Up: Pass Fail FIRED Barrel Horizontal, Bottom of Stock Down: Pass Page 2 of 2 Z101\DROPTEST_REV3.DOC