

GUN # A-14

DAT # 1 M/710 MAGNUM PRODUCTION RECEIVER INSERT

TRACKING # TLW1216

PROJECT #241314

SERIAL # 71126540

CAL 300 WIN MAG

NAME	DATE	TEST ACTIVITY	COMMENTS	ROUNDS AT START-0	
				RDS. FIRED	TOTAL RDS.
SW/BL	7/21/03	Head space	Min +.005		TLW1216A
SW/BL	7/21/03	Head space	Shoulder Gauge .221 will not close up		TLW1216A
SW/BL	7/21/03	Firing Pin Indent	.019-.019 .020 AVG .0193		TLW1216D
SW/BL	7/22/03	Trigger Pull	4.209, 4.302, 4.269 Avg. 4.26		TLW1216E
SW/BL	7/22/03	Sear Trigger Engagement	.0271, .0273, .0270 Avg. .02713		TLW1216E
SW/BL	7/22/03	Sear Lift	.0225		TLW1216E
SW/BL	7/22/03	Reset Sear Trigger Engagement	.0237, .0234, .0234 Avg. .0235		TLW1216E
SW/BL	7/22/03	Reset Trigger Pull	4.322, 5.466, 5.527 Avg. 5.105		TLW1216F
SW/BL	7/22/03	Firing Pin Head / Sear Engagement	.039		TLW1216E
SW/BL	7/23/03	Safety ON Forces	5.455, 5.425, 5.570 Avg. 5.483		TLW1216G
SW/BL	7/23/03	Safety OFF Forces	1.830, 1.675, 1.760 Avg. 1.755		TLW1216G
SW/BL	7/24/03	Bolt Lift	14.76, 14.64, 14.70 Avg. 14.70		TLW1216H
SW/BL	7/24/03	Bolt Close	5.38, 5.34, 5.26 Avg. 5.32		TLW1216H
SW/BL	7/24/03	Bolt Lift w/ Dummy	14.88, 15.26, 15.40 Avg. 15.18		TLW1216H
SW/BL	7/24/03	Bolt Close w/ Dummy	5.62, 5.60, 5.36 Avg. 5.52		TLW1216H
SW/BL	7/25/03	Magazine Spring Force	gauge 0.200 1.750 - 1.650 - 1.490 Avg. 1.630		TLW1216I
			gauge 1.0 4.320 - 5.325 - 5.605 Avg. 5.016		
SW/BL	7/29/03	Magazine Capacity Test	pass - weak ejection		TLW1216O
SW/BL	7/29/03	Chock ISS System	pass		TLW1216AI
SW/BL	7/29/03	Twist Rate	1 Turn 10" +.25		TLW1216N
SW/BL	7/30/03	Bore Diameter	Spec. .300/.301 Dimension .300		TLW1216L
SW/BL	8/6/03	Proof Test	OK		TLW1216B
SW/BL	8/6/03	Head space After Proof	Min +.006		TLW1216C
SW/BL	8/20/03	Inspection	Checked stock for cracks, stock has cracks		TLW1216K
SW/BL	9/11/03	SAAMI JAR-OFF TEST	PASS magazine latch broken		TLW1216X
SW/BL	9/12/03	SAAMI ROTATION TEST	PASS		TLW1216Y
PKR	9/11/03	Replaced Mag. Latch	with good one from B-15 stock		
SW/BL	9/14/03	SAAMI DROP TEST	PASS		TLW1216W
SW/BL	9/18/03	Extended 18" JAR-OFF TEST	PASS		TLW1216Z
SW/JS	9/18/03	EXTENDED 24" JAR-OFF TEST	PASS		TLW1216Z
SW/JS	9/19/03	EXTENDED 48" JAR-OFF TEST	PASS		TLW1216Z
SW/JS	9/22/03	BROKE PLASTIC RECEIVER INSERT	DO NOT SHOOT		TLW1216AR
B Lee	9/30/03	Exchanged Bolt Head	A-1 Bolt Head exchanged with A-14		

Logform

Confidential - Subject to Protective Order

Williams v. Remington

ET22315