

CONFIDENTIAL

Remington Arms Company Inc.
Research & Development Technical Center
315 West Ring Road
Elizabethtown, KY 42701

Clean & Inspect Checklist

Model: 710 Magnum

Project: 241314

Rifle: A-9

TLW #: TLW1216

Date: 9 / 8 / 03

Inspector: SW/BL

Round Level: 741

- ☒ Measure Headspace Min + .007
- ☒ Sear Engagement: 1st. .0260 2nd. .0259 3rd. .0259 Ave. .02593 spec- .020" to .025" 83
- ☒ Reset Sear Engagement if Required: 1st. .0223 2nd. .0224 3rd. .0226 Ave. .02243
- ☒ Trigger Pull: 1st. 4.478 2nd. 4.512 3rd. 4.462 Ave. 4.484 spec- 4 lb. to 5.5 lb.
- ☒ Reset Trigger Pull if Required: 1st. 4.309 2nd. 4.442 3rd. 4.334 Ave. 4.361
- ☒ Inspect cam surface, locking lugs and bolt stop for signs of excessive wear: Normal wear, wear on bolt latch
- ☒ Inspect stock for any signs of cracking or other failure. CRACKS in stock
- ☒ Other items of note: Top of magazine box has some protrusion, wear in magazine latch area Photo taken

TLW1216

Remington Confidential

ET22342