

GUN # A-1

SERIAL # 71126310

CAL 300 WIN MAG

DAT # 1 M / 710 MAGNUM PRODUCTION RECEIVER INSERT

TRACKING # TLW1216

PROJECT #241314

NAME	DATE	TEST ACTIVITY	COMMENTS	ROUNDS AT START-0	
				RDS. FIRED	TOTAL RDS.
SW/BL	7/21/03	Weight	8.401 TLW1216A M		
SW/BL	7/21/03	Headspace	Min + .001 TLW1216A		
SW/BL	7/21/03	Headspace Shoulder Gauge	.221 will not close up TLW1216A		
SW/BL	7/21/03	Firing Pin Indent	.020 - .020 - .019 Avg. .0196 TLW1216D		
SW/BL	7/22/03	Balance Point	From Butt Pad 19 1/2 TLW1216AN		
SW/BL	7/22/03	Trigger Pull	5.305, 5.378, 5.519 Avg. 5.400 TLW1216F		
SW/BL	7/22/03	Sear/Trigger Engagement	.0253 .0252 .0253 .02526 TLW1216E		
SW/BL	7/22/03	Sear Left	.0225 TLW1216E		
SW/BL	7/22/03	Firing Pin Head/Sear Engagement	.060 TLW1216E		
SW/BL	7/23/03	Safety ON Forces	6.035, 5.840, 5.850 Avg 5.908 TLW1216G		
SW/BL	7/23/03	Safety OFF Forces	2.045, 2.405, 2.300 Avg 2.250 TLW1216G		
SW/BL	7/24/03	Bolt Lift	16.32, 16.84, 16.14 Avg. 16.43 TLW1216H		
SW/BL	7/24/03	Bolt Closing	4.58, 4.96, 4.84 Avg 4.82 TLW1216H		
SW/BL	7/24/03	Bolt Lift w/Dummy	16.68, 14.74, 15.75 Avg. 15.72 TLW1216H		
SW/BL	7/24/03	Bolt Closing w/Dummy	5.34, 4.82, 5.12 Avg. 5.09 TLW1216H		
SW/BL	7/25/03	Magazine Spring forces	gauge 0.200 (1.620 - 1.785 Avg. 1.730 TLW1216I gauge 1.0 (4.520 - 4.870 Avg. 4.643)		
SW/BL	7/29/03	Magazine Capacity Test	pass - weak ejection TLW1216O		
SW/BL	7/29/03	Check ESS system	pass TLW1216AI		
SW/BL	7/29/03	Turn Rate	1 turn 10" + .25 TLW1216N		
SW/BL	7/30/03	Bore diameter	Spec 300/301 Dimension 300 TLW1216L		
SW/BL	7/30/03	Chamber Cast/measurements	See spread sheet TLW1216K		
SW/BL	7/30/03	Groove diameter	Spec. 308/309 Dimension 309 TLW1216M		
SW/BL	8/6/03	Proof Test	Hammer Bolt Break TLW1216B	1	1
SW/BL	8/6/03	Headspace After Proof	Min + .002 TLW1216C		
SW/BL	8/8/03	Basic Jack Function Test	ATF ATF TLW1216P	200	201
Phil B	8/12/03	Basic Shoulder Functioning Test	4 Malfunctions TLW1216Q	20	221
			1 - Round in Magazine stacked wrong		
			3 - Bolt Stop Failed (bolt came out)		
SW	8/19/03	Cleaned	TLW1216S		
SW/BL	8/20/03	Inspection	Headspace Min + .003 TLW1216S		
SW/BL	8/22/03	Accuracy Test	20 Rds 1 Bolt Stop Failed TLW1216T	20	241
SW/BL	8/26/03	Scope Endurance Test	Accuracy Before 30 Rds OK TLW1216AK	30	271
BL	8/27/03	Scope Endurance Test	From Jack 40 Rds OK	40	311
SW/BL	8/28/03	Scope Endurance Test	Accuracy After 30 Rds OK	30	341

Logform

Confidential - Subject to Protective Order

Williams v. Remington

ET22405