

CONFIDENTIAL

Remington Arms Company Inc.
Research & Development Technical Center
315 West Ring Road
Elizabethtown, KY 42701

Clean & Inspect Checklist

Model: 710 Magnum

Project: 241314

Rifle: A-6

TLW #: TLW1216

Date: 8 / 20 / 03

Inspector: SW/BL

Round Level: 221

- ☒ Measure Headspace min +.006
- ☒ Sear Engagement: 1st .0263 2nd .0262 3rd .0264 Ave. .0263 spec- .020" to .025"
- ☒ Reset Sear Engagement if Required: 1st .0234 2nd .0237 3rd .0235 Ave. .02353
- ☒ Trigger Pull: 1st 5.353 2nd 5.274 3rd 5.220 Ave. 5.282 spec- 4 lb. to 5.5 lb.
- ☒ Reset Trigger Pull if Required: 1st 4.934 2nd 5.104 3rd 4.826 Ave. 4.955
- ☒ Inspect cam surface, locking lugs and bolt stop for signs of excessive wear: wear on bolt stop
- ☒ Inspect stock for any signs of cracking or other failure. Lower corner of recoil bracket has cracks on stock
Crack on middle take down screw hole
- ☒ Other items of note: Top of magazine Box has some protrusion, wear in
magazine latch area

TLW1216

Remington Confidential

ET22427