

CONFIDENTIAL

Remington Arms Company Inc.
Research & Development Technical Center
315 West Ring Road
Elizabethtown, KY 42701

Clean & Inspect Checklist

Model: 710 Magnum

Project: 241314

Rifle: A-6

TLW #: TLW1216

Date: 10 / 08 / 03

Inspector: BLR

Round Level: 3761

☒ Measure Headspace min .006

☒ Sear Engagement: 1st. .0250 2nd. .0245 3rd. .0243 Ave. .0246 spec- .020" to .025" 83

☐ Reset Sear Engagement if Required: 1st. _____ 2nd. _____ 3rd. _____ Ave. _____

☒ Trigger Pull: 1st. 4.116 2nd. 4.143 3rd. 4.235 Ave. 4.164 spec- 4 lb. to 5.5 lb.

☐ Reset Trigger Pull if Required: 1st. _____ 2nd. _____ 3rd. _____ Ave. _____

☒ Inspect cam surface, locking lugs and bolt stop for signs of excessive wear: normal wear wear on bolt stop

☒ Inspect stock for any signs of cracking or other failure: cracks in stock

☒ Other items of

note: magazine box some protrusion

- Photos taken of chamber w/ scope 3 front / 3 rear

- Broken magazine latch / replaced with rifle A12 latch

TLW1216

Remington Confidential

ET22489