

4.197
4.382
4.296

CONFIDENTIAL

Remington Arms Company Inc.
Research & Development Technical Center
315 West Ring Road
Elizabethtown, KY 42701

Clean & Inspect Checklist

Model: 710 Magnum

Project: 241314

Rifle: A-6

TLW #: TLW1216

Date: 10 109 103

Inspector: B. Lee

Round Level: 4261

☒ Measure Headspace min + .006

☒ Sear Engagement: 1st. .0245 2nd. .0216 3rd. .0249 Ave. .0246 spec. .020" to .025" 83

☐ Reset Sear Engagement if Required: 1st. _____ 2nd. _____ 3rd. _____ Ave. _____

☒ Trigger Pull: 1st. 4.197 2nd. 4.382 3rd. 4.296 Ave. 4.296 spec. 4 lb. to 5.5 lb.

☐ Reset Trigger Pull if Required: 1st. _____ 2nd. _____ 3rd. _____ Ave. _____

☒ Inspect cam surface, locking lugs and bolt stop for signs of excessive wear: normal wear wear on bolt stop

☒ Inspect stock for any signs of cracking or other failure: cracks in stock

☒ Other items of note: magazin Box same protrusion
- Photos taken of chamber w/ scope 3 Front / 3 Rear

TLW1216

Remington Confidential

ET22501