

CONFIDENTIAL

Remington Arms Company Inc.
Research & Development Technical Center
315 West Ring Road
Elizabethtown, KY 42701

Clean & Inspect Checklist

Model: 710 Magnum

Project: 241314

Rifle: A-3

TLW #: TLW1216

Date: 8 / 20 / 03

Inspector: SW/BL

Round Level: 221

☒ Measure Headspace Min + .007

☒ Sear Engagement: 1st. .0270 2nd. .0280 3rd. .0277 Ave. .02783 spec- .020" to .025" 83

☒ Reset Sear Engagement if Required: 1st. .0245 2nd. .0243 3rd. .0247 Ave. .0245

☒ Trigger Pull: 1st. 4.184 2nd. 4.220 3rd. 4.118 Ave. 4.174 spec- 4 lb. to 5.5 lb.

☒ Reset Trigger Pull if Required: 1st. 4.032 2nd. 4.039 3rd. 4.023 Ave. 4.031

☒ Inspect cam surface, locking lugs and bolt stop for signs of excessive wear: _____

☒ Inspect stock for any signs of cracking or other failure. Lower corner of recoil bracket has cracks on stock, crack on middle take down screw hole.

☒ Other items of note: Top of magazine box has some protrusion, wear in magazine latch area

TLW1216

Remington Confidential

ET22558