

RIFLE # A-2
S.N. 71163358
CAL. 30 - 06 SPRG

M/710 EXTRUDED RECEIVER D.A.T.

PROJECT: #
TLW: # 1530

NAME	DATE	TEST ACTIVITY	COMMENTS	ROUNDS AT START-	
				RDS. FIRED	TOTAL RDS.
B.Lee	7-12-04	Initial Headspace			
B.Lee	7-13-04	Proof	min + .003		
B.Lee	7-13-04	Re-measure Headspace	OK	1	1
B.Lee	7-13-04	Indents	min + .002		
B.Lee	7-13-04	Engagement	.019 - .019 .018 Aug. .0186		
SW	7-14-04	Sear/Firing Pin Head Engagement	See data sheet		
SW	7-15-04	Trigger Pull	See data sheet		
BL	7-15-04	Safety On/Off Forces	See data sheet		
BL	7-15-04	Bolt opening/closing Forces	See data sheet		
SW	7-16-04	Sear Lift	See data sheet		
BL	8-5-04	2000 Basic Jack Function Test		80	81
JS	8-10-04	(Receiver Modified)	Machined chamber to aid in feeding ammo		
JS	8-12-04	2000 Basic Jack Function Test		120	201
SW/WH	8-12-04	Shoulder Function Test	0 Malfunction	20	221
BL/JS	8-12-04	Accuracy		20	241
SW	8-16-04	Clean + Inspect	OK Headspace Min + .003		
JS	8-24-04	Endurance Test	OK	500	741
SW	8-30-04	Clean + Inspect	OK Headspace Min + .003		
SW/JS	8-30-04	Semi Juv-Off	Pass		
SW/JS	8-30-04	Semi Rotation	Pass		
SW/JS	8-31-04	Semi Drop	Pass		
SW/JS	9-2-04	Extended Juv-Off	18" Pass		
SW/JS	9-2-04	Extended Juv-Off	24" Pass		
SW/JS	9-2-04	Extended Juv-Off	36" Failed		
SW	9-8-04	Put insert into A-14	Broken Insert from A-14 into A-2		

DAILY DATA SHEET

Remington Arms Confidential

Page 1

ET22750