

RIFLE # A-3
S.N. 71163365
CAL. 30 - 06 SPRG

M / 710 EXTRUDED RECEIVER D.A.T.

PROJECT: #
TLW: # 1530

NAME	DATE	TEST ACTIVITY	COMMENTS	ROUNDS AT START- RDS. FIRED		TOTAL RDS.
B.Lee	7-12-04	Initial Headspace	min+.004	TLW1530B		
B.Lee	7-13-04	Proof	OK	TLW1530C	1	1
B.Lee	7-13-04	Re-measure Headspace	min+.004	TLW1530D		
B.Lee	7-13-04	Indents	.026-.019-.020 Avg .0196	TLW1530E		
SW	7-14-04	Engagement	See data sheet	TLW1530F		
SW	7-15-04	Sear/Firing Pin Head Engagement	See data sheet	TLW1530G		
SW	7-15-04	Trigger Pull	See data sheet	TLW1530H		
BL	7-15-04	Safety on/off forces	See data sheet	TLW1530I		
BL	7-15-04	Bolt opening/closing forces	See data sheet	TLW1530J		
SW	7-16-04	Sear Lift	See data sheet	TLW1530F		
BL	8-5-04	2nd Basic Jack Function Test	mag box fell apart at 27 Rds	TLW1530N	80	81
JS	8-10-04	Modified Receiver	Machined chamber to aid in feeding	TLW1530N	120	201
BL	8-12-04	2nd Basic Jack Function Test		TLW1530N	20	221
SW/BL	8/13/04	Shoulder Function Test	0 Malfunctions	TLW1530O	20	241
BL/JS	8/13/04	Accuracy			20	
SW	8/16/04	Clean + Inspect	OK Headspace Min+.004	TLW1530R		
JS	8/24/04	Endurance	FTEXT1	TLW1530Q	500	741
SW	8/30/04	Clean + Inspect	OK Headspace Min+.003	TLW1530R		
BL	8-31-04	Magazine Release Latch	Broken at 840 Rds / replaced			
BL	8-31-04	Endurance	malfunctions / FTEXT1		500	1241
SW/BL	9/1/04	Clean + Inspect	OK Headspace Min+.005	TLW1530R		
BL	9/2/04	Endurance	6 FTEXT 7 FTEXT2	TLW1530Q	500	1741
SW/BL	9/2/04	Clean + Inspect	OK Headspace Min+.005	TLW1530R		
BL	9-6-04	Endurance	5 FTEXT	TLW1530Q	500	2241
SW/BL	9/8/04	Clean + Inspect	OK Headspace Min+.005	TLW1530R		

DAILY DATA SHEET

Remington Arms Confidential

Page 1

ET22768

Confidential - Subject to Protective Order

Williams v. Remington