

CONFIDENTIAL

Remington Arms Company Inc.
Research & Development Technical Center
315 West Ring Road
Elizabethtown, KY 42701

Clean & Inspect Checklist

Model: 710 EXTRUDED RECEIVER

Project: 241230

Rifle: A-3

TLW #: TLW1530

Date: 9 / 8 / 04

Inspector: SW

Round Level: 2341

- ☒ Measure Headspace Min + .005
- ☒ Sear Engagement: 1st. .0282 2nd. .0286 3rd. .0282 Ave. .0283 spec. .020" to .025" 83
- ☐ Reset Sear Engagement if Required: 1st. _____ 2nd. _____ 3rd. _____ Ave. _____
- ☒ Trigger Pull: 1st. 4.409 2nd. 4.438 3rd. 4.432 Ave. 4.430 spec. 4 lb. to 5.5 lb.
- ☐ Reset Trigger Pull if Required: 1st. _____ 2nd. _____ 3rd. _____ Ave. _____
- ☒ Inspect cam surface, locking lugs and bolt stop for signs of excessive wear: Locking lugs normal wear, bolt stop little wear
- ☒ Inspect stock for any signs of cracking or other failure. _____
- ☒ Other items of note: _____

TLW1216

Remington Confidential

ET22796