

RIFLE # A-6
S.N. 71163349
CAL. .270 WIN

M / 710 EXTRUDED RECEIVER D.A.T.

PROJECT: #
TLW: # 1530

NAME	DATE	TEST ACTIVITY	COMMENTS	ROUNDS AT START- RDS. FIRED		TOTAL RDS.
B-Lee	7-12-04	Initial Headspace	min .002			
B-Lee	7-13-04	Proof	OK			
B-Lee	7-13-04	Re-measure Headspace	min .003			
B-Lee	7-13-04	Indents	.019-.018-.018 Avg. .0183			
SW	7-14-04	Engagement	See data sheet			
SW	7-15-04	Sear/Firing Pin Head Engagement	See data sheet			
SW	7-15-04	Trigger Pull	See data sheet			
BL	7-15-04	Safety ON/OFF Forces	See data sheet			
BL	7-15-04	Bolt opening/closing Forces	See data sheet			
SW	7-16-04	Sear Lift	See data sheet			
SW	7-23-04	300 Rd Basic Jack Function Test	TLW1530N			
			Stopped Test after 100 rds (Bolt hard to open and hammer bolt back 34 times) SW/ML			
PKR	7/26/04	Inspect Chamber	- Check chamber w/borescope - Found very bad gouge around chamber - digital images taken	100		101
* USE GUN FOR DROP TESTING ONLY *						
SW/BL	8-4-04	SAAMI JAR-OFF TEST 12"	PASS			
SW/BL	8-4-04	SAAMI Rotation Test	PASS			
SW/BL	8-4-04	SAAMI Drop Test 48"	PASS Band scope			
SW/BL	8-4-04	Extended JAR-OFF TEST 18"	PASS			
SW/BL	8-4-04	" " " " 24"	PASS			
SW/BL	8-4-04	" " " " 36"	Fail Gun fired on Barrel Horizontal, left side of stock up and Barrel Horizontal, Bottom of stock down			
SW/BL	8-5-04	Extended Rotation Test	PASS			
BL/SW	8-5-04	Extended Drop Test	72" PASS Broken Tamy			

DAILY DATA SHEET

Remington Arms Confidential

Page 1

ET22843

Confidential - Subject to Protective Order

Williams v. Remington