

TLW 1530 AC

Project No. 241230

A-6

EXTENDED ROTATION TEST

Firecontrol No. A-6 Firecontrol Type: STANDARD Date: 8-5-04
 Dry Cycles/Rounds Completed: N/A Stock Type SYNTHETIC Engagement at Start 02033
 Model No. M/710 Serial No. 71163349 Engagement at End 0205
 Trigger Pull at Start of Test (1) 4.118 (2) 3.995 (3) 4.144 (4) 4.175 (5) 4.047 (6) 4.096
 Average Trigger Pull at Start of Test: 4.096 Std. Dev. of Trigger Pull at Start of Test: _____
 Trigger Pull at End of Test (1) 4.002 (2) 4.020 (3) 4.402 (4) 4.001 (5) 3.974 (6) 4.081
 Average Trigger Pull at End of Test: 4.081 Std. Dev. of Trigger Pull at End of Test: _____

Tester Initials: DL/SW

Additional Notes and Comments

. 270 win

SAAMI Specifications for Standard Rotation Test do not apply to this test.

Extended Rotation Test: Rest Firearm on the Butt end and allow Firearm to fall
 Drop - onto Tile Floor backed by Concrete. NO RUBBER MATT
 Firearm not ready to fire, Safe in "Safe" position, Fresh Primed Case
 in Chamber, Magazine loaded to capacity with Dummy Rounds.
 After each drop Fire Primed Case to verify firearm will still function.

"Rotation Test" (safety in "Safe" position) - one drop per orientation.

Note: for Firearms with the ISS system installed - The Firearms will be set with the
ISS system in the unlocked position for both orientations of the Rotation Test.

Orientation	ISS Unlocked	Comments
Firearm Vertical, Drop so left side of Stock is Up:	Pass <input checked="" type="checkbox"/> Fail <input type="checkbox"/>	
Firearm Vertical, Drop so right side of Stock is Up:	Pass <input checked="" type="checkbox"/> Fail <input type="checkbox"/>	

Notes: (continue on back of sheet if necessary)

Tester's Initials SW/BL