

RIFLE # A-8
S.N: 71163354
CAL. .270 WIN

M / 710 EXTRUDED RECEIVER D.A.T.

PROJECT: #
TLW: # 1530

NAME	DATE	TEST ACTIVITY	COMMENTS	ROUNDS AT START- RDS. FIRED	TOTAL RDS.
B.Lee	7-2-04	Initial Headspace	min+.002	TLW1530B	
B.Lee	7-3-04	PROOF	OK	TLW1530C	1
B.Lee	7-3-04	Remeasure Headspace	min+.002	TLW1530D	
B.Lee	7-13-04	Indents	.018-.018-.019 Avg. .0183	TLW1530E	
SW	7-14-04	Engagement	See data sheet	TLW1530F	
SW	7-15-04	Sear/Firing Pin Head Engagement	See data sheet	TLW1530G	
SW	7-15-04	Trigger Pull	See data sheet	TLW1530H	
BL	7-15-04	Safety on/off Forces	See data sheet	TLW1530I	
BL	7-15-04	Bolt Opening/Closing Forces	See data sheet	TLW1530J	
SW	7-16-04	Sear Lift	See data sheet	TLW1530F	
SW	7/23/04	300 Rd Basic Jack Function Test 0 Malfunctions	TLW1530N	200	201
SW/PR	7/26/04	30 Rd Shoulder Function Test 0 Malfunctions	TLW1530O	20	221
JK	7/26/04	Accuracy Testing	TLW1530P	20	241
SW	7/27/04	Cleaned & Inspected OK	TLW1530R		
BL	7/29/04	Extended Function & Endurance Test Bolt hand to close 4 times	TLW1530Q	500	741
BL	7/29/04	Clean & Inspected	TLW1530R		
SW/BL	8-4-04	SAAMI JAR-off Test 12" PASS	TLW1530Y		
BL/SW	8-4-04	SAAMI ROTATION TEST PASS	TLW1530Z		
BL/SW	8-4-04	SAAMI DROP TEST 48" PASS	TLW1530AA		
BL/SW	8-4-04	Extended JAR-off Test 18" PASS	TLW1530AB		
BL/SW	8-4-04	" " " " 24" PASS	TLW1530AB		
BL/SW	8-4-04	" " " " 36" Gun Fired on Barrel Horizontal, Bottom of	TLW1530AB		
		Stack up	TLW1530AB		
BL/SW	8-5-04	Extended Rotation Test PASS	TLW1530AC		
BL/SW	8-5-04	Extended Drop Test 72" Fail Gun Fired twice	TLW1530AD		
		Broken Insert previous Drop (SW)			

DAILY DATA SHEET

Remington Arms Confidential

Page 1

Confidential - Subject to Protective Order

Williams v. Remington

ET22889