

TLW 1530AB

Project No. 241230

300 Win Mag

EXTENDED JAR-OFF TESTING

Firecontrol No. A-13 Firecontrol Type: Standard Date: _____
Dry Cycles/Rounds Completed: _____ Stock Type Syn Engagement at Start _____
Model No. M/710 Serial No. 71163351 Engagement at End _____
Trigger Pull at Start of Test (1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (6) _____
Average Trigger Pull at Start of Test: _____ Std. Dev. of Trigger Pull at Start of Test: _____
Trigger Pull at End of Test (1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (6) _____
Average Trigger Pull at End of Test: _____ Std. Dev. of Trigger Pull at End of Test: _____

Tester Initials: _____

Additional Notes and Comments

PERFORM TESTING IN ITS ENTIRETY OR UNTIL THE GUN FAILS.**IF A GUN FAILS, FINISH DROPPING ALL ORIENTATIONS AT THAT HEIGHT, THEN STOP.***Specifications for Extended Jar-Off Test:*

Jar-Off Test: 6, 18, 24, 36 & 48-inch drop - onto 1" thick 85 Durometer (Shore A) Rubber Matt. Firearm ready to fire, Safe in "Fire" position, Fresh Primed Case in Chamber, Magazine loaded to capacity with Dummy Rounds. After each drop, fire Primed Case to verify firearm will still function.

all drops (safety in "Fire" position) - one drop per orientation.

Note: for Firearms with the ISS system installed - The ISS will be set in the unlocked position for all six orientations of the Jar-Off Test

Page 1 of 4

Z101\EXTENDED JAR-OFF TEST_REV5.DOC

ET22997

A-13

TLW _____

Project No. _____

EXTENDED JAR-OFF TESTING**6 INCH EXTENDED JAR-OFF TEST**

Engagement before 6"- 1. _____, 2. _____, 3. _____ Avg. _____

Trigger Movement before 6"- 1. _____, 2. _____, 3. _____ Avg. _____

Trigger Pull before 6"- 1. _____, 2. _____, 3. _____, 4. _____, 5. _____, Avg. _____

Orientation

ISS Unlocked

Comments

Barrel Vertical, Muzzle Up: Pass _____ Fail _____

Barrel Vertical, Muzzle Down: Pass _____ Fail _____

Barrel Horizontal, Left side of Stock Up: Pass _____ Fail _____

Barrel Horizontal, Right side of Stock Up: Pass _____ Fail _____

Barrel Horizontal, Bottom of Stock Up: Pass _____ Fail _____

Barrel Horizontal, Bottom of Stock Down: Pass _____ Fail _____

Engagement after 6"- 1. _____, 2. _____, 3. _____ Avg. _____

Trigger Movement after 6"- 1. _____, 2. _____, 3. _____ Avg. _____

Trigger Pull after 6"- 1. _____, 2. _____, 3. _____, 4. _____, 5. _____, Avg. _____

18 INCH EXTENDED JAR-OFF TEST9.2-04
SW/SWEngagement before 18"- 1. 0.0276, 2. 0.0278, 3. 0.0277 Avg. 0.02770

Trigger Movement before 18"- 1. _____, 2. _____, 3. _____ Avg. _____

Trigger Pull before 18"- 1. 5.267, 2. 5.255, 3. 5.472, 4. 5.300, 5. 5.296, Avg. 5.338Orientation

ISS Unlocked

Comments

Barrel Vertical, Muzzle Up: Pass ☒ Fail _____Barrel Vertical, Muzzle Down: Pass ☒ Fail _____Barrel Horizontal, Left side of Stock Up: Pass ☒ Fail _____Barrel Horizontal, Right side of Stock Up: Pass ☒ Fail _____Barrel Horizontal, Bottom of Stock Up: Pass ☒ Fail _____Barrel Horizontal, Bottom of Stock Down: Pass ☒ Fail _____Engagement after 18"- 1. 0.0282, 2. 0.0282, 3. 0.0282 Avg. 0.02820

Trigger Movement after 18"- 1. _____, 2. _____, 3. _____ Avg. _____

Trigger Pull after 18"- 1. 4.431, 2. 4.464, 3. 4.476, 4. 4.458, 5. 4.485, Avg. 4.463

A-13

TLW _____

Project No. _____

EXTENDED JAR-OFF TESTING *Date- 2 Sep 04***24 INCH EXTENDED JAR-OFF TEST**Engagement before 24"- 1. 0.0282, 2. 0.0282, 3. 0.0282 Avg. 0.02820

Trigger Movement before 24"- 1. _____, 2. _____, 3. _____ Avg. _____

Trigger Pull before 24"- 1. 4.813, 2. 4.938, 3. 4.830, 4. 4.831, 5. 4.769, Avg. 4.836**Orientation****ISS Unlocked****Comments**

Barrel Vertical, Muzzle Up:	Pass ☒ Fail _____	
Barrel Vertical, Muzzle Down:	Pass ☒ Fail _____	
Barrel Horizontal, Left side of Stock Up:	Pass ☒ Fail _____	
Barrel Horizontal, Right side of Stock Up:	Pass ☒ Fail _____	
Barrel Horizontal, Bottom of Stock Up:	Pass ☒ Fail _____	
Barrel Horizontal, Bottom of Stock Down:	Pass ☒ Fail _____	

Engagement after 24"- 1. 0.0287, 2. 0.0287, 3. 0.0286 Avg. 0.02866

Trigger Movement after 24"- 1. _____, 2. _____, 3. _____ Avg. _____

Trigger Pull after 24"- 1. 5.397, 2. 5.427, 3. 5.443, 4. 5.465, 5. 5.469, Avg. 5.440**36 INCH EXTENDED JAR-OFF TEST**9.2 04
SW/JWEngagement before 36"- 1. 0.0287, 2. 0.0287, 3. 0.0286 Avg. 0.02866

Trigger Movement before 36"- 1. _____, 2. _____, 3. _____ Avg. _____

Trigger Pull before 36"- 1. 5.397, 2. 5.427, 3. 5.443, 4. 5.465, 5. 5.469, Avg. 5.440**Orientation****ISS Unlocked****Comments**

Barrel Vertical, Muzzle Up:	Pass ☒ Fail _____	
Barrel Vertical, Muzzle Down:	Pass ☒ Fail _____	
Barrel Horizontal, Left side of Stock Up:	Pass ☒ Fail _____	
Barrel Horizontal, Right side of Stock Up:	Pass ☒ Fail _____	
Barrel Horizontal, Bottom of Stock Up:	Pass ☒ Fail _____	
Barrel Horizontal, Bottom of Stock Down:	Pass ☒ Fail _____	

Engagement after 36"- 1. 0.0286, 2. 0.0288, 3. 0.0287 Avg. 0.02870

Trigger Movement after 36"- 1. _____, 2. _____, 3. _____ Avg. _____

Trigger Pull after 36"- 1. 5.066, 2. 5.110, 3. 5.097, 4. 5.075, 5. 5.114, Avg. 5.092

A-13

TLW _____

Project No. _____

EXTENDED JAR-OFF TESTING

9/3/04

OW/JW

48 INCH EXTENDED JAR- OFF TESTEngagement before 48"- 1. .0281, 2. .0288, 3. .0287 Avg. .02870

Trigger Movement before 48"- 1. _____, 2. _____, 3. _____ Avg. _____

Trigger Pull before 48"- 1. 5.066, 2. 5.110, 3. 5.097, 4. 5.075, 5. 5.114 ,Avg. 5.092**Orientation****ISS Unlocked****Comments**Barrel Vertical, Muzzle Up: Pass ☒ Fail _____Barrel Vertical, Muzzle Down: Pass ☒ Fail _____Barrel Horizontal, Left side of Stock Up: Pass ☒ Fail _____Barrel Horizontal, Right side of Stock Up: Pass ☒ Fail _____Barrel Horizontal, Bottom of Stock Up: Pass ☒ Fail _____Barrel Horizontal, Bottom of Stock Down: Pass ☒ Fail _____

light indent on primed case

Broken Insert Tang

83

Engagement after 48"- 1. .0301, 2. .0304, 3. .0302 Avg. 3.023

Trigger Movement after 48"- 1. _____, 2. _____, 3. _____ Avg. _____

Trigger Pull after 48"- 1. 5.158, 2. 5.222, 3. 5.111, 4. 5.287, 5. 5.236 , Avg. 5.203