	TLW
	Project No. 341095
S.A.A.M.I.	JAR-OFF, DROP & ROTATION TEST
8	
G-UN 	Firecontrol Type: 5+24davd Date: 12/4/01
y Cycles/Rounds Completed:	Stock Type Engagement at Start
odel No. 710 Serial N	lo. 71001633 Engagement at End
igger Pull at Start of Test (1)	(2) (3) (4) (5) (6)
verage Trigger Pull at Start of Test:	Std. Dev. of Trigger Pull at Start of Test:
igger Pull at End of Test (1)	(2) (3) (4) (5) (6)
erage Trigger Pull at End of Test:	Std. Dev. of Trigger Pull at End of Test:
•	Tester Initials: SW
, A	dditional Notes and Comments
dew angle connect	0V \
·	
For additional detailares the	proper procedures to be used for this Test Procedure refer to:
Firearm 1 Chamber,	rop onto 1" thick 85 durameter (Shore A) Rubber Matt eady to fire, Safe in "Fire" position, Fresh Primed Case in Magazine loaded to capacity with Dummy Rounds. In drop, fire Primed Case to verify firearm will still function.
	fety in "Fire" position) - one drop per orientation.
Note: for Firearms with th	te ISS system installed – The ISS will be set in the unlocked
<u>position</u>	for all six orientations of the Jar-Off Test
O <u>rientation</u> IS	S Unlocked Comments
Barrel Vertical, Muzzle Up:	Pass Fail
Barrel Vertical, Muzzle Down:	Pass Fail
Barrel Horizontal, Left side of Stock Up:	Pass Fail
Barrel Horizontal, Right side of Stock Up.	/
Barrel Horizontal, Bottom of Stock Up:	Pass / Fail
Barrel Horizontal, Bottom of Stock Down	
Sure invitation, bottom of stock bown	: Pass V Fail
in the second	
	Page 1
	Z101\DROPTEST_REV3.E