

2 PLACE (.01) - TOLERANCE $\pm .015$
3 PLACE (.001) - TOLERANCE $\pm .010$
& ON FRACTIONAL DIMENSIONS $\pm 1/64$
& ON ANGULAR DIMENSIONS $\pm 00^{\circ} - 30'$
FINISHES ARE DESIGNATED BY ROOT MEAN
SQUARE (R.M.S.) MICRO-INCH ROUGHNESS
VALUES AND ARE THE MAXIMUM ROUGHNESS
ACCEPTABLE. UNLESS OTHERWISE SPECIFIED,
FINISH ROUGHNESS TO BE $\sqrt{125}$ OR BETTER.

FINISH ROUGHNESS TO BE $125\sqrt{\quad}$ OR BETTER.

(3)
(9)
(9)
(9)

10

83

FD-302 (Rev. 11-27-70)

REMINGTON SUPERSEDES C-300485 REV. E		SCALE 4:1		NUMBER C-300485	
REFERENCE DCR# E-00041		TITLE CONNECTOR			
CHK. BY DATE JWR 11-08-00		DRN. BY DATE JAW 08-25-00		DES. BY DATE	
PART USE CONNECTOR		PART NO. 300485		MODEL 710	

T V N

Confidential - Subject to Protective Order
Williams v. Remington