	TLW <u>0452</u>
	Project No. 24/267
	S.A.A.M.I. JAR-OFF, DROP & ROTATION TEST
Firec Dry Mod Trigg Aver Trigg	UNontrol No
	Additional Notes and Comments
	For additional details on the proper procedures to be used for this fest Procedure refer to:
	ANSI / SAAMI Z299.5-1990 SAAMI Specifications for Standard Jar-Off Test
S. S	Jar-Off Test: 12-inch drop + onto 1" thick 85 durameter (Shore A) Rubber Matt Fireatim ready to fire, Safe in "Fire" position, Fresh Primed Case in Chamber, Magazine loaded to capacity with Dummy Rounds. After each drop, fire Primed Case to verify firearm will still function. 12 inch drop (safety in "Fire" position) - one drop per orientation. Note for Firearms with the ISS system installed - The ISS will be set in the unlocked
	position for all six orientations of the Jar-Off Test
	Orientation ISS Unlocked Comments Barrel Vertical, Muzzle Up: Pass Fail Barrel Vertical, Muzzle Down: Pass Fail Barrel Vertical, Muzzle Down: Pass Fail Barrel Horizontal, Left side of Stock Up: Pass Fail Barrel Horizontal, Right side of Stock Up: Pass Fail Barrel Horizontal, Bottom of Stock Up: Pass Fail Barrel Horizontal, Bottom of Stock Down: Pass Fail
	Page 1 of 2 Z101\DROPTEST_REV3.DOC

٩

ET30069

•

ł

Confidential - Subject to Protective Order Williams v. Remington

-		TLW	0452
,		Project No	
	S.A.A.M.I. JAR-OFF, DROP & R	OTATION TEST	· · · · · · · · · · · · · · · · · · ·
	SAAMI Specifications for Standar	rd Drop Test:	
<u>Drop Test</u> :	48-inch drop - onto 1" thick 85 dura Firearm not ready to fire, Safe in "S in Chamber, Magazine loaded to cap After each drop Fire Primed Case to	afe" position, Fresh P pacity with Dummy Ro	rimed Case unds.
48	inch drop (safety in "Safe" position) - or	ne drop per orientation	•
<u>Note: for Fi</u>	<u>rearms with the ISS system installed – T</u>	he Firearms will be se	t with the
<u>ISS syst</u>	em in the unlocked position for all six o	rientations of the Drot	o Test
Orientation	ISS Unlocked	Comm	ients
Barrel Vertical, Muzzle U	p: Pass Fail		
Barrel Vertical, Muzzle D	Down: Pass Fail		
Barrel Horizontal, Left sig	de of Stock Up: Pass Fail	Lear Senew B	roke Replace Schew
Barrel Horizontal, Right s	side of Stock Up: Pass Fail		
Barrel Horizontal, Bottom	n of Stock Up: Pass Fail		,
Barrel Horizontal, Botton	n of Stock Down: Pass		· · ·
SAAMI Specif	ications for Standard Rotation Test	ូល្អភិវ ស្រ្តីដ៏កំណើង ស្រ្តីកំពុង ស្រ កម្ពុជា	
<u>Rotation Test</u> "Ro	Rest Firearm on the Butt end and al Drop, onto 1" thick 85 durameter (Firearm not ready to fire, Safe in "S in Chamber, Magazine loaded to ca After each drop Fire Primed Case to tation Test" (safety in "Safe" position) -	(Shore A) Rubber Matt Safe" position, Fresh F pacity with Dummy Ra o verify firearm will sti one drop per orientati	Primed Case punds. Il function. on.
- 282	Firearms <u>with the ISS system installed</u> –		
	em in the unlocked position for both orie	/	
Orienta		Ca	omments
Firearm Vertical, Drop so		·	
Firearm Vertical, Drop so	o right side of Stock is Up: Pass Fail		· · · · · · · · · · · · · · · · · · ·
Notes: (continue on back of	sheet if necessary)		
			· · · · · · · · · · · · · · · · · · ·
		· · · · · · · · · · · · · · · · · · ·	
		Tester's Initials	JW/BL
	·		

مدرج

.

1.

ET30070

Confidential - Subject to Protective Order Williams v. Remington