

TLW 0452

Project No. 241267

S.A.A.M.I. JAR-OFF, DROP & ROTATION TEST

Firecontrol No. A-7 Firecontrol Type: STANDARD Date: 04-10-01
 Dry Cycles/Rounds Completed: _____ Stock Type 4.17.0 Lic Engagement at Start .0180
 Model No. M/7 Serial No. 7758643 Engagement at End .0178
 Trigger Pull at Start of Test (1) 4.0 (2) 4.0 (3) 4.25 (4) 4.0 (5) 3.75 (6) 4.0
 Average Trigger Pull at Start of Test: 4.0 Std. Dev. of Trigger Pull at Start of Test: _____
 Trigger Pull at End of Test (1) 4.5 (2) 4.25 (3) 4.25 (4) 4.5 (5) 4.5 (6) 4.5
 Average Trigger Pull at End of Test: 4.41 Std. Dev. of Trigger Pull at End of Test: _____

Tester Initials: RVL

Additional Notes and Comments

For additional details on the proper procedures to be used for this Test Procedure refer to:

ANSI/SAAMI Z299.5-1990

SAAMI Specifications for Standard Jar-Off Test:

Jar-Off Test: 12-inch drop - onto 1" thick 85 durometer (Shore A) Rubber Matt
Firearm ready to fire, Safe in "Fire" position, Fresh Primed Case in
Chamber, Magazine loaded to capacity with Dummy Rounds.
After each drop, fire Primed Case to verify firearm will still function.

12 inch drop (safety in "Fire" position) - one drop per orientation.

Note for Firearms with the ISS system installed - The ISS will be set in the unlocked
position for all six orientations of the Jar-Off Test

<u>Orientation</u>	<u>ISS Unlocked</u>	<u>Comments</u>
Barrel Vertical, Muzzle Up:	Pass <input checked="" type="checkbox"/> Fail _____	_____
Barrel Vertical, Muzzle Down:	Pass <input checked="" type="checkbox"/> Fail _____	_____
Barrel Horizontal, Left side of Stock Up:	Pass <input checked="" type="checkbox"/> Fail _____	_____
Barrel Horizontal, Right side of Stock Up:	Pass <input checked="" type="checkbox"/> Fail _____	_____
Barrel Horizontal, Bottom of Stock Up:	Pass <input checked="" type="checkbox"/> Fail _____	_____
Barrel Horizontal, Bottom of Stock Down:	Pass <input checked="" type="checkbox"/> Fail _____	_____

S.A.A.M.I. JAR-OFF, DROP & ROTATION TEST

SAAMI Specifications for Standard Drop Test:

Drop Test: 48-inch drop - onto 1" thick 85 durameter (Shore A) Rubber Matt
Firearm not ready to fire, Safe in "Safe" position, Fresh Primed Case
in Chamber, Magazine loaded to capacity with Dummy Rounds.
After each drop Fire Primed Case to verify firearm will still function.

48 inch drop (safety in "Safe" position) - one drop per orientation.

Note: for Firearms with the ISS system installed - The Firearms will be set with the
ISS system in the unlocked position for all six orientations of the Drop Test

Orientation	ISS Unlocked	Comments
Barrel Vertical, Muzzle Up:	Pass <input checked="" type="checkbox"/> Fail <input type="checkbox"/>	
Barrel Vertical, Muzzle Down:	Pass <input checked="" type="checkbox"/> Fail <input type="checkbox"/>	
Barrel Horizontal, Left side of Stock Up:	Pass <input checked="" type="checkbox"/> Fail <input type="checkbox"/>	
Barrel Horizontal, Right side of Stock Up:	Pass <input checked="" type="checkbox"/> Fail <input type="checkbox"/>	
Barrel Horizontal, Bottom of Stock Up:	Pass <input checked="" type="checkbox"/> Fail <input type="checkbox"/>	
Barrel Horizontal, Bottom of Stock Down:	Pass <input checked="" type="checkbox"/> Fail <input type="checkbox"/>	

SAAMI Specifications for Standard Rotation Test:

Rotation Test: Rest Firearm on the Butt end and allow Firearm to fall
Drop onto 1" thick 85 durameter (Shore A) Rubber Matt
Firearm not ready to fire, Safe in "Safe" position, Fresh Primed Case
in Chamber, Magazine loaded to capacity with Dummy Rounds.
After each drop Fire Primed Case to verify firearm will still function.

"Rotation Test" (safety in "Safe" position) - one drop per orientation.

Note: for Firearms with the ISS system installed - The Firearms will be set with the
ISS system in the unlocked position for both orientations of the Rotation Test.

Orientation	ISS Unlocked	Comments
Firearm Vertical, Drop so left side of Stock is Up:	Pass <input checked="" type="checkbox"/> Fail <input type="checkbox"/>	
Firearm Vertical, Drop so right side of Stock is Up:	Pass <input checked="" type="checkbox"/> Fail <input type="checkbox"/>	

Notes: (continue on back of sheet if necessary)

Tester's Initials JW/BL