

GUN# M-L  
SERIAL # 71147414  
CAL- 30.06 SPRG.

REMINGTON M/710  
NON-ISS BOLT PLUG  
DAILY TEST DATA SHEET

TRACKING # TLW1349  
PROJECT # MAYFIELD SUPPORT

| NAME    | DATE     | TEST ACTIVITY           | COMMENTS                                                                                     | ROUNDS AT START- | Ø          |
|---------|----------|-------------------------|----------------------------------------------------------------------------------------------|------------------|------------|
|         |          |                         |                                                                                              | RDS. FIRED       | TOTAL RDS. |
| J. Sims | 12/5/03  | INITIAL HEADSPACE       | 003                                                                                          |                  |            |
| J. Sims | 12/5/03  | PROOF TEST              | OK                                                                                           |                  |            |
| J. Sims | 12/5/03  | HEADSPACE AFTER PROOF   | 003                                                                                          | 1                | 1          |
| J. Sims | 12/5/03  | FIRING PIN INDENT       | 020, 021, 022                                                                                |                  |            |
|         |          | TRIGGER/SEAR ENGAGEMENT | eng. 0308, 0309, 0308 Avg. 0306 / Sear lift .0152 / reset eng. .021, .0197, .0201 Avg. .0202 |                  |            |
| DL/JS   | 12-8-03  | TRIGGER PULL            | 5.329-4.379-4.194 Avg. 4.368                                                                 |                  |            |
| P. Lee  | 12-8-03  | JACK FUNCTION TEST      | NO JACK FUNCTION                                                                             |                  |            |
| BL/JS   | 12-8-03  | SETUP FOR SAAMI TESTING | Scope mount 25 in lb / scope 40 in lb / take down                                            | 40               | 41         |
| BL/JS   | 12-8-03  | SAAMI ROTATION W/SCOPE  | Pass Rotation                                                                                |                  |            |
| BL/JS   | 12-9-03  | Re-measure              | engage - trigger pull                                                                        |                  |            |
| BL/JS   | 12-9-03  | SAAMI JARR-OFF W/SCOPE  | pass jar-off                                                                                 |                  |            |
| BL/JS   | 12-9-03  | Re-measure              | engagement - trigger pull                                                                    |                  |            |
| BL/JS   | 12-10-03 | SAAMI DROP W/SCOPE      | pass drop w/ scope                                                                           |                  |            |
| BL/JS   | 12-10-03 | Re-measure              | engagement - trigger pull                                                                    |                  |            |
| BL/JS   | 12-10-03 | RESET TO STD. SPECS.    | reset eng. 0226, 0215, 0217 Avg. 0219                                                        |                  |            |
|         |          |                         | Trigger Pull 4.765-4.367-4.294-4.375-4.280 Avg. 4.444                                        |                  |            |

THIS SHEET IS TO ACCOMPANY THE FIREARM AT ALL TIMES THROUGHOUT TESTING

FORMS.XLS

ET33802

Confidential - Subject to Protective Order

Williams v. Remington