

GUN# A-4  
SERIAL # 71147418  
CAL- 30.06 SPRG.

REMINGTON M710  
NON-ISS BOLT PLUG  
DAILY TEST DATA SHEET

TRACKING # TLW1349  
PROJECT # MAYFIELD SUPPORT

| NAME    | DATE     | TEST ACTIVITY           | COMMENTS                                                                                          | ROUNDS AT START- |            |
|---------|----------|-------------------------|---------------------------------------------------------------------------------------------------|------------------|------------|
|         |          |                         |                                                                                                   | RDS. FIRED       | TOTAL RDS. |
| J. Sims | 12/5/03  | INITIAL HEADSPACE       | .002                                                                                              |                  |            |
| J. Sims | 12/5/03  | PROOF TEST              | .002                                                                                              | 1                | 1          |
| J. Sims | 12/5/03  | HEADSPACE AFTER PROOF   | .002                                                                                              |                  |            |
| J. Sims | 12/5/03  | FIRING PIN INDENT       | .018, .021, .020                                                                                  |                  |            |
| BL/JS   | 12-8-03  | TRIGGER/SEAR ENGAGEMENT | eng. .027, .025, .027 Avg - .027 / Sear Lift - .0159 / Reset Eng. .0201, .0204, .0207 Avg - .0204 |                  |            |
| BL/JS   | 12-8-03  | TRIGGER PULL            | 4.28-4.67-4.392- Avg 4.605 / 4.25-4.676                                                           |                  |            |
| B.Lee   | 12-8-03  | JACK FUNCTION TEST      | No Jack Functions 25in lb / scope                                                                 | 40               | 41         |
| BL/JS   | 12-8-03  | SETUP FOR SAAMI TESTING | Torque Scope Mount 25in lb / scope 40in lb / Take down screws Top 40in lb - lower 25in lb         |                  |            |
| BL/JS   | 12-8-03  | SAAMI ROTATION W/SCOPE  | Pass Rotation                                                                                     |                  |            |
| BL/JS   | 12-9-03  | Re-measure              | engagement - trigger Pull                                                                         |                  |            |
| BL/JS   | 12-9-03  | SAAMI JARR-OFF W/SCOPE  | pass jar-off                                                                                      |                  |            |
| JS/BL   | 12-9-03  | Re-measure              | engagement - trigger Pull                                                                         |                  |            |
| JS/BL   | 12-10-03 | SAAMI DROP W/SCOPE      | pass drop w/ scope                                                                                |                  |            |
| JS/BL   | 12-10-03 | Re-measure              | engagement - trigger pull                                                                         |                  |            |
| JS/BL   | 12-10-03 | RESET TO STD. SPECS.    | reset eng. .0275, .0219, .0273 Avg .025<br>Trigger Pull - 4.426-4.324-4.469-4.623-4.565 Avg 4.481 |                  |            |

THIS SHEET IS TO ACCOMPANY THE FIREARM AT ALL TIMES THROUGHOUT TESTING

FORMS.XLS

ET33812