

GUN# **A-2**
SERIAL # **71146951**
CAL- 30.06 SPRG.

REMINGTON M/710
NON-ISS BOLT PLUG
DAILY TEST DATA SHEET

TRACKING # TLW1349
PROJECT # MAYFIELD SUPPORT

NAME	DATE	TEST ACTIVITY	COMMENTS	ROUNDS AT START-	
				RDS. FIRED	TOTAL RDS.
J. Sims	12/5/03	INITIAL HEADSPACE	.002		
J. Sims	12/5/03	PROOF TEST	OK	1	1
J. Sims	12/5/03	HEADSPACE AFTER PROOF	.002		
J. Sims	12/5/03	FIRING PIN INDENT	.021, .021, .022		
		TRIGGER/SEAR ENGAGEMENT	Pass .031, .033, .032 Avg. -		
BL/JS	12-8-03	TRIGGER PULL	1/Sec 1.1ft - .0124 / Reset avg. .0206, .0203, .0205 Avg. -		
BL/JS	12-8-03	JACK FUNCTION TEST	4.038 - 4.541 - 4.841 - Avg 4.806 Set - 4.070		
BL/JS	12-8-03	SETUP FOR SAAMI TESTING	NO BALL FUNCTIONS Torque Screw mount 25 in 16 / scope variable / Take down screws Top 40 in 16 - Lower 25 in 16	40	41
BL/JS	12-8-03	SAAMI ROTATION W/SCOPE	Pass Rotation		
BL/JS	12-9-03	Re-measure	engagement - trigger		
BL/JS	12-9-03	SAAMI JARR-OFF W/SCOPE	pass jar-off		
BL/JS	12-9-03	Re measure	engagement - trigger pull		
BL/JS	12-10-03	SAAMI DROP W/SCOPE	pass drop w/ scope		
BL/JS	12-10-03	Re measure	engagement - trigger ball		
BL/JS	12-10-03	RESET TO STD. SPECS.	reset avg - .0223, .0229, .0226 Avg. .0226		
			Trigger Pull 4.483 - 4.403 - 4.489 - 4.445 - 4.436 Avg 4.451		

THIS SHEET IS TO ACCOMPANY THE FIREARM AT ALL TIMES THROUGHOUT TESTING

FORM 510

ET33817