

GUN# **B-1**
SERIAL # **7114201**
CAL- 270 WIN.

REMINGTON M710
NON-ISS BOLT PLUG
DAILY TEST DATA SHEET

TRACKING # TLW1349
PROJECT # MAYFIELD SUPPORT

NAME	DATE	TEST ACTIVITY	COMMENTS	ROUNDS AT START-	
				RDS. FIRED	TOTAL RDS.
J. Sims	12/5/03	INITIAL HEADSPACE	.004		
J. Sims	12/5/03	PROOF TEST	OK	1	1
J. Sims	12/5/03	HEADSPACE AFTER PROOF	.004		
J. Sims	12/5/03	FIRING PIN INDENT	.021, .019, .021		
	12-8-03	TRIGGER/SEAR ENGAGEMENT	15.004, .019, .021 Avg. - 15.004 / 15.004 / 15.004 Avg. - .0207		
DL/JS	12-8-03	TRIGGER PULL	4.137 - 4.281 - 4.869 Avg 4.229 Set 4.002		
J. Sims	12/8/03	JACK FUNCTION TEST	Shot 4.137	40	41
BL/JS	12-8-03	SETUP FOR SAAMI TESTING	Torque Specs adjust 20 in lb / scope 40 in lb / Take down screws Top 40 in lb - Lower 25 in lb		
JS/BL	12-9-03	SAAMI ROTATION W/SCOPE	Pass Rotation		
JS/BL	12-9-03	Re-measure	engagement - trigger pull		
JS/BL	12-9-03	SAAMI JARR-OFF W/SCOPE	Pass jar-off		
JS/BL	12-9-03	Re-measure	engagement - trigger pull		
JS/BL	12-10-03	SAAMI DROP W/SCOPE	Pass drop w/ scope		
JS/BL	12-10-03	Re-measure	engagement - trigger pull		
JS/BL	12-10-03	RESET TO STD. SPECS	Reset Eng. .0219, .0219, .0219 Avg. .0219 Trigger Pull - 4.518 - 4.506 - 4.339 - 4.304 - 4.258 Avg 4.485		

THIS SHEET IS TO ACCOMPANY THE FIREARM AT ALL TIMES THROUGHOUT TESTING

FORMS.XLS

ET33827