

GUN# **B-2**
SERIAL # 71143578
CAL- 270 WIN.

**REMINGTON M/710
NON-ISS BOLT PLUG
DAILY TEST DATA SHEET**

TRACKING #TLW1349
PROJECT # MAYFIELD SUPPORT

CAL-270 WIN.				ROUNDS AT START-	
NAME	DATE	TEST ACTIVITY	COMMENTS	RDS. FIRED	TOTAL RDS.
J. Sims	12/5/03	INITIAL HEADSPACE	.001	1	1
J. Sims	12/5/03	PROOF TEST	O.K.		
J. Sims	12/5/03	HEADSPACE AFTER PROOF	.007		
J. Sims	12/5/03	FIRING PIN INDENT	.020, .020, .021		
		TRIGGER/SEAR ENGAGEMENT	eng. .015, .022, .029 Avg. - / Sear lift. .0152 / reset eng. .0203, .0202, .0204 Avg. .0203		
BL/JS	12-8-03	TRIGGER PULL	4.955-4.600 = 4.684 - Avg 4.759 / Set 4.008	40	41
J Sims	12/8/03	JACK FUNCTION TEST	Shot clean		
BL/JS	12-8-03	SETUP FOR SAAMI TESTING	Torgue Scope Mount 25 in lb / Scope 40 in lb / Take down screws Top 40 in lb - Lower 25 in lb		
BL/JS	12-9-03	SAAMI ROTATION W/SCOPE	Pass Rotation		
BL/JS	12-9-03	Re-measure	engagement - trigger pull		
BL/JS	12-9-03	SAAMI JARR-OFF W/SCOPE	pass jar off		
BL/JS	12-9-03	Re-measure	engagement - trigger pull		
BL/JS	12-10-03	SAAMI DROP W/SCOPE	pass drop w/scope		
BL/JS	12-10-03	Remeasure	engagement - trigger pull		
BL/JS	12-10-03	RESET TO STD. SPECS.	reset eng. - .0226, .0221, .0223 Avg. .0223 Trigger Pull - 4.202 - 4.203 - 4.461 - 4.501 Avg. 4.460		

THIS SHEET IS TO ACCOMPANY THE FIREARM AT ALL TIMES THROUGHOUT TESTING

FORMS.XLS

Confidential - Subject to Protective Order

ET33832