

GUN# **B-5**
SERIAL # 71143698
CAL- 270 WIN.

REMINGTON M/710 NON-ISS BOLT PLUG DAILY TEST DATA SHEET

TRACKING # TLW1349
PROJECT # MAYFIELD SUPPORT

NAME	DATE	TEST ACTIVITY	COMMENTS	ROUNDS AT START-	TOTAL RDS.
				RDS. FIRED	
J. Sims	12/5/03	INITIAL HEADSPACE	.002		
J. Sims	12/5/03	PROOF TEST	- Hard to open -	1	1
J. Sims	12/5/03	HEADSPACE AFTER PROOF	.002		
J. Sims	12/5/03	FIRING PIN INDENT	.020 .019 .020		
		TRIGGER/SEAR ENGAGEMENT	Pos. .0293, .0295, .0298 Avg. / Seat lift - .0189 / reset Eng. .0201, .0203, .0204 Avg. -		
BL/JS	12-8-03	TRIGGER PULL	4.669 - 4.660 - 4.734 - Avg 4.667	40	41
J. Sims	12/8/03	JACK FUNCTION TEST	Shot 10 Rds		
BL/JS	12-8-03	SETUP FOR SAAMI TESTING	Torque Scope mount 25 in lb / scope 10 in lb / Take down scope Pop 40 in lb - Lower 25 in lb		
BL/JS	12-9-03	SAAMI ROTATION W/SCOPE	Pass Rotation		
BL/JS	12-9-03	Remasure	Engagement / trigger pull		
BL/JS	12-9-03	SAAMI JARR-OFF W/SCOPE	pass jar - off		
BL/JS	12-9-03	Remas sure	engagement - trigger pull		
BL/JS	12-10-03	SAAMI DROP W/SCOPE	pass drop w/ scope		
BL/JS	12-10-03	Remas sure	engagement - trigger pull		
BL/JS	12-10-03	RESET TO STD. SPECS.	reset Eng. = .0216, .0227, .0214 Avg. .0219 Trigger Pull = 4.476 - 4.520 - 4.539 - 4.499 - 4.496 - Avg 4.506		

THIS SHEET IS TO ACCOMPANY THE FIREARM AT ALL TIMES THROUGHOUT TESTING

FORMS.XLS

Confidential - Subject to Protective Order

ET33847