

GUN# A-1
SERIAL # 71147415
CAL- 30.06 SPRG.

REMINGTON M710
NON-ISS BOLT PLUG
DAILY TEST DATA SHEET

TRACKING # TLW1349
PROJECT # MAYFIELD SUPPORT

NAME	DATE	TEST ACTIVITY	COMMENTS	ROUNDS AT START-	
				RDS. FIRED	TOTAL RDS.
J. Sims	12/5/03	INITIAL HEADSPACE	.002	1	1
J. Sims	12/5/03	PROOF TEST	OK		
J. Sims	12/5/03	HEADSPACE AFTER PROOF	.002		
J. Sims	12/5/03	FIRING PIN INDENT	.020, .019, .019		
J. Sims	12-8-03	TRIGGER/SEAR ENGAGEMENT	eng. .0258, .0256, .026 - Avg. .0258; Sear lift .0157; reset eng. .0209, .0201, .0209 Avg		
BL/JS	12-5-03	TRIGGER PULL	5.198 - 4.993 - 4.886 - Avg 5.019 - Avg 4.640 - 3.998 - 3.972 Avg 4.183 Set 4.114	40	41
BLer	12-8-03	JACK FUNCTION TEST	NO MALFUNCTIONS		
JS/BL	12-8-03	SETUP FOR SAAMI TESTING	Torques: Scope mount 25 in lb / Scope 40 in lb / Take down screws top 40 in lb / Lower 25 in lb.		
BL/JS	12-8-03	SAAMI ROTATION W/SCOPE	Pass rotation		
BL/JS	12-9-03	Re-measure	engagement - trigger pull		
BL/JS	12-9-03	SAAMI JARR-OFF W/SCOPE	Pass jarr-off		
BL/JS	12-9-03	Re-measure	engagement - Trigger Pull		
BL/JS	12-10-03	SAAMI DROP W/SCOPE	pass drop w/ scope		
BL/JS	12-10-03	re measure	engagement / trigger pull		
BL/JS	12-10-03	RESET TO STD. SPECS.	reset eng. .0263, .0229, .0219 Avg. .0224 Trigger Pull 4.53 - 4.485 - 4.304 - 4.345 - 4.272 Avg. 4.412		

THIS SHEET IS TO ACCOMPANY THE FIREARM AT ALL TIMES THROUGHOUT TESTING

FORMS.XLS

ET33852

Confidential - Subject to Protective Order

Williams v. Remington