

502

710 TRAIL & PILOT TEST				PRELIMINARY MEASUREMENTS & CHECKS										BLUE INDICATES BELOW SPEC. MIN. VALUE RED INDICATES ABOVE SPEC. MIN. VALUE											
11/00																									
TEST LAB TRACKING NUMBER: TLW0300																									
PROOF TEST & MAGNAFLUX COMPLETED AT MAYFIELD																									
GUN ID #	SERIAL NUMBER	PROOF STAMP	MAGNAFLUX STAMP	HEADSPACE, REM. SPEC GAUGES	TRIGGER PULL WITH SPRING SCALE			FIRING PIN INDENT WITH COPPER CRUSHERS			SEAR TO TRIGGER ENGAGEMENT			SEAR LIFT											
					TLW0300G	TLW0300J	LBS.	TLW0300H	TLW0300I	TLW0300K	TLW0300L	TLW0300M	TLW0300N	TLW0300O	TLW0300P	TLW0300Q		TLW0300R							
					1	2	3 AVERAGE	1	2	3 AVERAGE	1	2	3 AVERAGE	1	2	3 AVERAGE									
A-1	71001378	YES	YES	MIN+.002	5	4.75	5.25	5.00	0.018	0.017	0.017	0.0173	0.0282	0.0289	0.0284	0.0283	0.0152	0.0167	0.0158	0.0155					
A-2	71001425	Y	Y	BELOW MIN	4.75	5.5	5.25	5.17	0.017	0.016	0.016	0.0163	GUN POLLED OUT OF TEST FOR BELOW MIN CHAMBER 11/04/00												
A-3	71001350	Y	Y	MIN+.003	6.5	5.5	5.25	5.75	0.019	0.019	0.019	0.0190	0.0238	0.0247	0.0239	0.0241	0.0154	0.0156	0.0161	0.0157					
A-4	71001500	Y	Y	MIN+.003	4.25	4.25	4.5	4.33	0.018	0.018	0.018	0.0180	0.0228	0.0236	0.0227	0.0238	0.0178	0.0177	0.0184	0.0171					
A-5	71001287	Y	Y	MIN+.002	5.75	5.5	5.5	5.58	0.018	0.018	0.018	0.0183	TRIGGER TO THE RIGHT OF CENTER IN THE TRIGGER GUARD (RETURN TO MAYFIELD)												
A-6	71001486	Y	Y	MIN+.002	6.5	6	6.75	6.08	0.018	0.018	0.018	0.0180	0.0238	0.0246	0.0241	0.0241	0.0132	0.0143	0.0144	0.0140					
A-7	71001262	Y	Y	MIN+.002	4.75	4.5	4.75	4.67	0.017	0.016	0.016	0.0167	0.0238	0.0246	0.0241	0.0241	0.0132	0.0143	0.0144	0.0138					
A-8	71001351	Y	Y	MIN+.004	5.5	5.5	5.75	5.58	0.018	0.018	0.018	0.0180	0.0238	0.0246	0.0241	0.0241	0.0132	0.0143	0.0144	0.0138					
A-9	71001372	Y	Y	MIN+.002	5.25	4.75	5.25	5.03	0.018	0.018	0.018	0.0183	0.0238	0.0246	0.0241	0.0241	0.0132	0.0143	0.0144	0.0138					
A-10	71001230	Y	Y	MIN+.002	5.5	5.5	5.5	5.50	0.018	0.018	0.018	0.0183	0.0238	0.0246	0.0241	0.0241	0.0132	0.0143	0.0144	0.0138					
A-11	71001432	Y	Y	MIN+.002	3.75	4	4	3.92	0.018	0.018	0.018	0.0183	0.0238	0.0246	0.0241	0.0241	0.0132	0.0143	0.0144	0.0138					
A-12	71001387	Y	Y	MIN+.002	4.5	4.5	4.5	4.50	0.018	0.018	0.018	0.0183	0.0238	0.0246	0.0241	0.0241	0.0132	0.0143	0.0144	0.0138					
A-13	71001132	Y	Y	MIN+.002	5.5	5.25	5	5.23	0.018	0.017	0.017	0.0173	0.0238	0.0246	0.0241	0.0241	0.0132	0.0143	0.0144	0.0138					
A-14	71001004	Y	Y	MIN+.003	4.75	3.75	4.25	4.25	0.018	0.018	0.018	0.0180	GUN FOLLOWED DOWN DURING 10 RD. LANYARD TEST (OUT OF TEST)												
A-15	71001484	Y	Y	MIN+.003	4.5	4.75	4.75	4.67	0.017	0.017	0.017	0.0170	BOLT STOP BROKE (OUT OF TEST 11/04/00)												
A-16	71001138	Y	Y	MIN+.002	5	4.5	4.75	4.75	0.017	0.017	0.017	0.0170	0.0212	0.0213	0.0201	0.0206	0.0154	0.0158	0.0149	0.0154					
A-17	71001415	Y	Y	MIN+.002	5	4.75	5	4.92	0.017	0.016	0.016	0.0163	0.0238	0.0246	0.0241	0.0241	0.0132	0.0143	0.0144	0.0138					
A-18	71001430	Y	Y	MIN+.001	4.5	4.75	4.75	4.67	0.018	0.017	0.017	0.0173	TRIGGER LOCATED TO THE LEFT OF CENTER OF TRIGGER GUARD (RETURNED TO MAYFIELD)												
A-19	71001323	Y	Y	MIN+.002	5	4.5	4.5	4.67	0.019	0.018	0.018	0.0183	0.0238	0.0246	0.0241	0.0241	0.0132	0.0143	0.0144	0.0138					
A-20	71001384	Y	Y	MIN+.003	5.5	5.5	5.75	5.58	0.017	0.017	0.017	0.0170	0.0301	0.0304	0.0297	0.0299	0.0123	0.0131	0.0131	0.0127					
A-21	71001210	Y	Y	MIN+.002	4.25	4.5	4.5	4.42	0.017	0.018	0.018	0.0177	0.0189	0.02	0.0195	0.0198	0.0143	0.0137	0.0142	0.0141					
A-22	71001250	Y	Y	MIN+.003	4.5	4.75	4.75	4.67	0.017	0.017	0.017	0.0170	0.0254	0.0274	0.0262	0.0262	0.0120	0.0122	0.0125	0.0125					
A-23	71001216	Y	Y	MIN+.003	4	4.5	4	4.17	0.019	0.017	0.018	0.0180	0.0301	0.0297	0.0287	0.0287	0.0120	0.0123	0.0134	0.0129					
A-24	71001224	Y	Y	MIN+.003	5	4.5	4.5	4.67	0.019	0.018	0.018	0.0183	0.0317	0.0323	0.0308	0.0316	0.0123	0.0118	0.0118	0.0122					
A-25	71001383	Y	Y	MIN+.002	4.5	4.25	4.25	4.33	0.018	0.018	0.018	0.0180	0.0259	0.0265	0.0257	0.0259	0.0152	0.0145	0.0145	0.0148					
A-26	71001130	Y	Y	MIN+.001	FIREARM FOLLOWED DOWN DURING 10 RD. LANYARD TEST (OUT OF TEST 11/04/00)										TRIGGER LOCATED IN A NORMAL & CENTERED LOCATION (RETURNED TO MAYFIELD)										
A-27	71001365	Y	Y	MIN+.002	4.75	5	5.25	5.00	0.019	0.018	0.018	0.0183	0.0305	0.0317	0.0314	0.0312	0.0158	0.014	0.0134	0.0144					
A-28	71001188	Y	Y	MIN+.002	4.25	4.5	4.25	4.33	0.019	0.018	0.018	0.0183	0.0293	0.0299	0.0294	0.0295	0.0111	0.0105	0.0110	0.0119					
A-29	71001214	Y	Y	MIN+.001	5.75	5.75	5.25	5.59	0.018	0.018	0.018	0.0180	0.0297	0.0304	0.0311	0.0304	0.013	0.0142	0.0143	0.0138					
A-30	71001387	Y	Y	MIN+.002	4.75	5.25	4.75	4.92	0.018	0.018	0.018	0.0183	0.0318	0.0325	0.0308	0.0327	0.0142	0.0141	0.0145	0.0148					
					TEST AVERAGE				TEST AVERAGE				TEST AVERAGE				TEST AVERAGE								
					4.92				0.0178				0.0282				0.0145								
					SPEC = 4.0 TO 5.0 LBS.				SAAMI MIN = .017				SPEC = .020 TO .025				SPEC = .005 TO .015								

83

Confidential - Subject to Protective Order
Williams v. Remington

ET34189