

Remington Arms
MayfieldQuality Manual 6-2
Appendix A
Form C-1036

First Article Inspection -Mayfield Results

Part Number
Part Name300336
FIRING PIN HEADDrawing #
Rev. LevelC-300336
IVendor
Date Received
Lot #MEGAMET
6/22/00
N/A

SAMPLES						Average	Min	Max	
#	Feature Name	#1	#2	#3	#4	#5			
1	.276 +/- .002	0.276	0.276	0.276	0.276	0.276	0.276	0.276	0.276 ** Gage pin
2	.440 +/- .003	0.441	0.441	0.441	0.440	0.442	0.441	0.440	0.442 caliper
3	.275 +/- .005	0.276	0.276	0.276	0.277	0.276	0.276	0.276	0.277 caliper
4	.170 +/- .005	0.169	0.169	0.171	0.170	0.169	0.170	0.169	0.171 caliper
5	.332 +/- .005	0.330	0.329	0.329	0.329	0.329	0.329	0.329	0.330 caliper
6	.130 +/- .005	0.132	0.130	0.131	0.128	0.127	0.130	0.127	0.132 caliper
7	.150 +/- .005	0.146	0.148	0.145	0.147	0.148	0.147	0.145	0.148 caliper
8	.170 +/- .005	0.167	0.169	0.168	0.167	0.168	0.168	0.167	0.169 caliper
9	.232 typ	0.229	0.230	0.230	0.228	0.227	A	A	A comp
10	Profile	A	A	A	A	A	A	A	A comp
11	full radius	A	A	A	A	A	A	A	A comp
12	full radius	A	A	A	A	A	A	A	A comp
13	.250 RAD	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
14	.345 RAD	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
15	.2200 +/- .0015	0.2210	0.2208	0.2228	0.2206	0.2212	0.2213	0.2206	0.2228 **comp
16	#12-28 unf 2-B	A	A	A	A	A	A	A	A thr gage
17	.114 +/- .005	0.113	0.115	0.116	0.118	0.115	0.115	0.113	0.118 comp
18	.050 +/- .005	0.053	0.052	0.053	0.052	0.053	0.053	0.052	0.053 comp
19	.135 R	0.133	0.133	0.130	0.131	0.133	A	A	A comp
20	.020 R	A	A	A	A	A	A	A	A comp
21	.020 R	A	A	A	A	A	A	A	A comp
22	.010 R	A	A	A	A	A	A	A	A comp
23	63.5 deg	63.4	63.4	63.5	63.4	63.4	63.42	63.4	63.5 comp
24	.043 +/- .005	0.046	0.046	0.045	0.048	0.045	0.046	0.045	0.048 comp
25	HRC 42-47	43.7	46.5	42.3	43.8	46.0	44.5	42.3	46.5 rockwell
26							#DIV/0!	0.00	0.00
27							#DIV/0!	0.0000	0.0000
28							#DIV/0!	0.0000	0.0000
29							#DIV/0!	0.0000	0.0000
30							#DIV/0!	0.0000	0.0000

Inspected By
Approved By
Rejected By

John Stairs

6/24/00

Date
DateRevised By: M. Goelmboski
Revision Date: 2/14/00

710-300336

ET06117