

3024

710 TRAIL & PILOT TEST				PRELIMINARY MEASUREMENTS & CHECKS				BLUE INDICATES BELOW SPEC. RED INDICATES ABOVE SPEC.																								
TEST LAB TRACKING NUMBER: TLW0300																																
PROOF TEST & MAGNAFLUX COMPLETED AT MAYFIELD																																
GWR ID #	SERIAL NUMBER	PROOF STAMP	MAGNAFLUX STAMP	HEADSPACE, REM. SPEC GAUGES	TRIGGER PULL WITH SPRING SCALE				FIRING PIN INDENT WITH COPPER CRUSHERS				SEAR TO TRIGGER ENGAGEMENT				SEAR LIFT															
					TLW0300G				TLW0300H				TLW0300I				TLW0300J															
					1	2	3	AVERAGE	1	2	3	AVERAGE	1	2	3	AVERAGE	1	2	3	AVERAGE												
A-1	71001378	YES	YES	MIN+.002	5	4.75	5.25	5.00	0.018	0.017	0.017	0.0173	0.0282	0.0233	0.0233	0.0238	0.0152	0.0167	0.0168	0.0158												
A-2	71001425	Y	Y	BELOW MIN	4.75	5.5	5.25	5.17	0.017	0.018	0.018	0.018	0.0108	0.0238	0.0247	0.0239	0.0241	0.0154	0.0168	0.0161	0.0157											
A-3	71001360	Y	Y	MIN+.003	5.5	5.5	5.25	5.75	0.019	0.018	0.019	0.019	0.0180	0.0238	0.0247	0.0239	0.0241	0.0154	0.0168	0.0161	0.0157											
A-4	71001500	Y	Y	MIN+.003	4.25	4.25	4.5	4.33	0.019	0.018	0.019	0.018	0.0180	0.0238	0.0247	0.0239	0.0241	0.0154	0.0168	0.0161	0.0157											
A-5	71001257	Y	Y	MIN+.002	5.75	5.5	5.25	5.57	0.019	0.018	0.019	0.018	0.0180	0.0238	0.0247	0.0239	0.0241	0.0154	0.0168	0.0161	0.0157											
A-6	71001465	Y	Y	MIN+.002	6.5	6	6.75	6.03	0.018	0.018	0.019	0.018	0.0180	0.0238	0.0247	0.0239	0.0241	0.0154	0.0168	0.0161	0.0157											
A-7	71001292	Y	Y	MIN+.002	4.75	4.5	4.75	4.67	0.017	0.018	0.019	0.018	0.0177	0.0238	0.0247	0.0239	0.0241	0.0154	0.0168	0.0161	0.0157											
A-8	71001351	Y	Y	MIN+.004	5.8	5.5	6.75	5.83	0.018	0.019	0.019	0.019	0.0187	0.0238	0.0247	0.0239	0.0241	0.0154	0.0168	0.0161	0.0157											
A-9	71001372	Y	Y	MIN+.002	6.25	4.75	5.25	5.53	0.018	0.018	0.019	0.018	0.0180	0.0238	0.0247	0.0239	0.0241	0.0154	0.0168	0.0161	0.0157											
A-10	71001296	Y	Y	MIN+.002	5.5	5.5	5.5	5.53	0.018	0.018	0.019	0.018	0.0183	0.0274	0.0292	0.0292	0.0292	0.0138	0.0143	0.0133	0.0142											
A-11	71001432	Y	Y	MIN+.002	3.75	4	4	3.92	0.018	0.018	0.019	0.018	0.0187	0.0318	0.0314	0.0316	0.0317	0.0144	0.0142	0.0143	0.0143											
A-12	71001387	Y	Y	MIN+.002	4.5	4.5	4.5	4.50	0.019	0.018	0.017	0.017	0.0177	0.0299	0.0302	0.0302	0.0302	0.0118	0.0139	0.0138	0.0131											
A-13	71001132	Y	Y	MIN+.002	5.5	5.25	5	5.25	0.018	0.017	0.017	0.017	0.0173	0.0299	0.0302	0.0302	0.0302	0.0118	0.0139	0.0138	0.0131											
A-14	71001084	Y	Y	MIN+.003	4.75	3.75	4.25	4.25	0.018	0.018	0.018	0.018	0.0180	0.0318	0.0318	0.0318	0.0318	0.0143	0.0143	0.0143	0.0143											
A-15	71001484	Y	Y	MIN+.003	4.5	4.75	4.75	4.67	0.017	0.017	0.017	0.017	0.0170	0.0312	0.0313	0.0301	0.0308	0.0159	0.0149	0.0134	0.0134											
A-16	71001139	Y	Y	MIN+.002	6	4.5	4.75	4.73	0.017	0.017	0.017	0.017	0.0170	0.0312	0.0313	0.0301	0.0308	0.0159	0.0149	0.0134	0.0134											
A-17	71001415	Y	Y	MIN+.002	5	4.75	6	4.92	0.017	0.016	0.016	0.016	0.0163	0.0238	0.0238	0.0238	0.0238	0.0143	0.0136	0.0134	0.0134											
A-18	71001439	Y	Y	MIN+.001	4.5	4.75	4.75	4.67	0.018	0.017	0.017	0.017	0.0173	0.0278	0.0278	0.0278	0.0278	0.0143	0.0136	0.0148	0.0141											
A-19	71001375	Y	Y	MIN+.002	5	4.5	4.5	4.67	0.018	0.018	0.018	0.018	0.0183	0.0278	0.0278	0.0278	0.0278	0.0143	0.0136	0.0148	0.0141											
A-20	71001394	Y	Y	MIN+.003	5.5	5.5	5.75	5.53	0.017	0.017	0.017	0.017	0.0170	0.0301	0.0304	0.0297	0.0301	0.0128	0.0123	0.0131	0.0127											
A-21	71001218	Y	Y	MIN+.002	4.25	4.5	4.5	4.42	0.017	0.018	0.018	0.018	0.0177	0.0189	0.02	0.0185	0.0180	0.0143	0.0137	0.0142	0.0141											
A-22	71001250	Y	Y	MIN+.003	4.5	4.75	4.75	4.67	0.017	0.017	0.017	0.017	0.0170	0.0254	0.0274	0.0262	0.0263	0.0128	0.0122	0.0125	0.0125											
A-23	71001218	Y	Y	MIN+.003	4	4.5	4	4.17	0.018	0.017	0.018	0.018	0.0180	0.0301	0.0297	0.0297	0.0301	0.0128	0.0123	0.0134	0.0129											
A-24	71001234	Y	Y	MIN+.003	5	4.5	4.5	4.67	0.018	0.018	0.018	0.018	0.0183	0.0317	0.0325	0.0309	0.0315	0.0128	0.0123	0.0134	0.0129											
A-25	71001383	Y	Y	MIN+.002	4.5	4.25	4.25	4.33	0.018	0.018	0.018	0.018	0.0180	0.0269	0.0273	0.0267	0.0269	0.0152	0.0147	0.0145	0.0145											
A-26	71001136	Y	Y	MIN+.001	FIREARM FOLLOWED DOWN DURING 10 RD. LANYARD TEST (OUT OF TEST 11/04/00)								0.018	0.018	0.018	0.018	0.0187	0.0305	0.0317	0.0314	0.0312	0.0158	0.0144	0.0134	0.0144							
A-27	71001385	Y	Y	MIN+.002	4.75	5	5.25	5.08	0.019	0.018	0.019	0.018	0.0183	0.0293	0.0299	0.0294	0.0298	0.0111	0.0108	0.0119	0.0110											
A-28	71001108	Y	Y	MIN+.002	4.25	4.5	4.25	4.33	0.018	0.018	0.018	0.018	0.0180	0.0297	0.0304	0.0311	0.0304	0.0142	0.0143	0.0138	0.0138											
A-29	71001214	Y	Y	MIN+.001	5.75	5.75	5.25	5.60	0.018	0.018	0.019	0.019	0.0180	0.0297	0.0304	0.0311	0.0304	0.0142	0.0143	0.0138	0.0138											
A-30	71001387	Y	Y	MIN+.002	4.75	5.25	4.75	4.92	0.018	0.019	0.019	0.019	0.0187	0.0318	0.0328	0.0333	0.0325	0.0141	0.0145	0.0146	0.0146											
TEST AVERAGE					4.92				TEST AVERAGE				0.0178				TEST AVERAGE				0.0248				TEST AVERAGE				0.0140			
SPEC. = 4.0 TO 5.0 LBS.									SAAMI MIN. = .017								SPEC. = .020 TO .025								SPEC. = .006 TO .018							

33