

**Snedeker, Jim**

---

**From:** Keeney, Mike  
**Sent:** Thursday, November 02, 2000 9:45 AM  
**To:** Franz, Scott; Bristol, II Ronald H.; Russo, Alfred D.; Trull, John C.; Golemboski, Matt R.; Zajk, Joseph J; Diaz, Danny; Danner, Dale; Snedeker, Jim  
**Subject:** RE: M/710 T & P Plan

A few comments:

The sample size requirement is 200, Mayfields intent was to produce up to 300 samples but the minimum is 200.

Any reason for the 10 round lanyard test? Mayfield is proof and function testing all of the rifles at their facility.

Minimum average Firing Pin Indent is .015", per our EET/DAT data and follow up analysis.

-----Original Message-----

**From:** Franz, Scott  
**Sent:** Wednesday, November 01, 2000 5:26 PM  
**To:** Bristol, II Ronald H.; Russo, Alfred D.; Trull, John C.; Golemboski, Matt R.; Zajk, Joseph J; Diaz, Danny; Keeney, Mike; Danner, Dale; Snedeker, Jim; Franz, Scott  
**Subject:** M/710 T & P Plan  
**Importance:** High

Attached is the final M/710 T & P test plan that we will execute to. Please review and get back if you have any issues or questions prior to test start. T & P activity will start this Friday with a Marketing evaluation of both product and packaging. T & P test and measurement activity will start Saturday.

Scott

<< File: M710\_TP\_TESTPLAN\_Rev4 >>