

CONFIDENTIAL

Remington Arms Company Inc.
RESEARCH & DEVELOPMENT TECHNICAL CENTER
315 WEST RING ROAD
ELIZABETHTOWN, KY 42701

Clean & Inspect Checklist

Model: 710 Short Action Caliber 243 & 308

Project: 241429

TLW #: TLW1876

Date: ____/____/____

Gun Test # ____

S/N ____

Round Level: ____

Inspector: ____

- ☐ Measure Headspace ____
- ☐ Check Takedown Screw Torque @ Disassembly: Frt ____ , Center ____ , Rear ____
- ☐ Sear Engagement: 1st. ____ 2nd. ____ 3rd. ____ Ave. ____ spec- .020" to .025"
- ☐ Reset Sear Engagement if Required: 1st. ____ 2nd. ____ 3rd. ____ Ave. ____
- ☐ Trigger Pull: 1st. ____ 2nd. ____ 3rd. ____ Ave. ____ spec- 4 lb. to 5.5 lb.
- ☐ Reset Trigger Pull if Required: 1st. ____ 2nd. ____ 3rd. ____ Ave. ____
- ☐ Inspect Magazine components for wear or damage

- ☐ Other items of note: _____

- ☐ Torque Takedown Screws @ Reassembly: SPEC- Frt- 50 in lbs, Center- 30-35 in lbs, Rear- 15 in lbs.

TLW1876

Remington Confidential