

ETE00000441

M/710 EXTRUDED RECEIVER T&P								
TLW 1689 G								
FIRING PIN HEAD ENGAGEMENT								
30-06			270 CAL			7MM RM		
RIFLE #	1	2	RIFLE #	1	2	RIFLE #	1	2
A1	0.085	LESS THAN .011	A11	0.080	LESS THAN .011	A21	0.084	LESS THAN .011
A2	0.085	LESS THAN .011	A12	0.084	0.014	A22	0.088	0.012
A3	0.086	LESS THAN .011	A13	0.086	0.016	A23	0.085	LESS THAN .011
A4	0.087	LESS THAN .011	A14	0.085	LESS THAN .011	A24	0.087	0.014
A5	0.086	0.014	A15	0.086	0.012	A25	0.089	0.012
A6	0.084	0.015	A16	0.083	0.015	A26	0.088	LESS THAN .011
A7	0.089	LESS THAN .011	A17	0.086	LESS THAN .011	A27	0.089	LESS THAN .011
A8	0.084	LESS THAN .011	A18	0.084	0.014	A28	0.082	LESS THAN .011
A9	0.085	0.014	A19	0.083	LESS THAN .011	A29	0.088	LESS THAN .011
A10	0.086	LESS THAN .011	A20	0.086	LESS THAN .011	A30	0.084	0.012
300 WM								
RIFLE #	1	2	* SEAR TO SLOT (1)					
			* FIRING PIN HEAD TO SLOT (2)					
A31	0.086	LESS THAN .011						
A32	0.086	LESS THAN .011						
A33	0.089	LESS THAN .011						
A34	0.087	LESS THAN .011						
A35	0.086	0.016						
A36	0.085	LESS THAN .011						
A37	0.083	0.012						
A38	0.085	LESS THAN .011						
A39	0.085	LESS THAN .011						
A40	0.089	LESS THAN .011						