

**CONFIDENTIAL**

Remington Arms Company Inc.  
RESEARCH & DEVELOPMENT TECHNICAL CENTER  
315 WEST RING ROAD  
ELIZABETHTOWN, KY 42701

**ABUSIVE TESTING****IMPACT TESTING**

Elimination of the Bushnell scope and addition of the iron sights results in a significant gun weight change. To verify that this weight change did not alter the shock sensitivity of the firearm 9 rifles were subjected to standard SAAMI Jar-Off, Drop and Rotation tests. All guns had fire controls adjusted to minimum process specification for trigger pull and engagement before the start of each major drop phase (Jar-Off, Drop and Rotation). Measurements were rechecked at the conclusion of each major test phase. The procedures as outlined by SAAMI and documented in the Test Plan was followed completely.

**Results:**

No inadvertent discharges occurred on any of the 9 rifles tested during any phase of testing.

|                     | <u>Number Guns Tested</u> | <u>Number Guns Passed</u> |
|---------------------|---------------------------|---------------------------|
| SAAMI Jar-Off Test  | 9                         | 9                         |
| SAAMI Rotation Test | 9                         | 9                         |
| SAAMI Drop Test     | 9                         | 9                         |

**ACCURACY TESTING:****POINT OF IMPACT/SIGHT ADJUSTMENT TEST**

An accuracy test at 100 yards was conducted in E-town's long range to insure that each rifles Point of Impact (POI) can be adjusted to coincide with the Point of Aim (POA) using the supplied iron sights. A major emphasis is placed on the ability to adjust the POI to the POA with enough sight adjustment remaining to compensate for varying distances and load configurations. As stated earlier a total of three iterations were required to confirm that sight adjustment was adequate. Remington ammo R30065 (180 grain PSP Core Lock) was used for all three iterations.

**Procedure:**

A special target is used (1 ft. dia. black bull) to aid visibility due to the range involved. The 6 o'clock position on the bull is used for the point of aim. See the Test Plan (Part B) for a description of the procedures and sight pictured used.

May 2011 Trial & Pilot Test Remington M710 Centerfire Rifle w/Iron Sights;  
R & D Technical Center Project No. 241095; TI.W0395, TI.W0405, TI.W 0505  
file: E:\Atlas3\710\ Trial & Pilot\_3006 Iron Sight Guns\M710\_T&P\_REPORT\_JUNE26\_Rev0.doc

Page 8

**CONFIDENTIAL**

REDACTED

Subject to Protective Order - Williams v. Remington

**BARBER 5.30.06R0003390**

ETE00001769